Needle Valve (Straight Body, Hard Seat)



Description & Features:

- Excellent flow regulation and leak tight
- The one-piece body construction (no welding) provides strength, safety and corrosion resistance
- "Slow opening" prevents sudden pressure surge and instrument damage
- Materials include carbon steel, carbon steel NACE, stainless steel, stainless steel NACE
- Available in Hard Seat (6,000 and 10,000 psi)
- ASME B1.20.1 compliant
- CRN registered
- 5 year warranty

Applications:

 Highly reliable throttle and block valve for gas or liquid service in severe duty oil and gas installations including refineries and processing plants as well as water treatment plants, power plants and hydraulic applications

Order Codes (products in bold are normally stock in North America)

IPT Connection	Material	Max. Pressure	Code	NPT Connection	Material	Max. Pressure	Code
1/4" Female x		6,000 psi	NVA5020	1/4" Female x	ĺ	6,000 psi	NVA5020
1/4" Female		10,000 psi	NVA6020	1/4" Female		10,000 psi	NVA6020
1/4" Male x		6,000 psi	NVA5000	1/4" Male x	Carbon Steel (NACE Tip)	6,000 psi	NVA5000
1/4" Female		10,000 psi	NVA6000	1/4" Female		10,000 psi	NVA6000
3/8" Female x		6,000 psi	NVA5024	3/8" Female x		6,000 psi	NVA5024
3/8" Female		10,000 psi	NVA6024	3/8" Female		10,000 psi	NVA6024
3/8" Male x		6,000 psi	NVA5004	3/8" Male x		6,000 psi	NVA5004
3/8" Female		10,000 psi	NVA6004	3/8" Female		10,000 psi	NVA6004
1/2" Female x		6,000 psi	NVA5021	1/2" Female x		6,000 psi	NVA502
1/2" Female		10,000 psi	NVA6021	1/2" Female		10,000 psi	NVA602
1/2" Male x		6,000 psi	NVA5001	1/2" Male x		6,000 psi	NVA500
1/2" Female	O ante an Otract	10,000 psi	NVA6001	1/2" Female		10,000 psi	NVA600
3/4" Female x	Carbon Steel	6,000 psi	NVA5022	3/4" Female x		6,000 psi	NVA502
1/2" Female		10,000 psi	NVA6022	1/2" Female		10,000 psi	NVA602
3/4" Male x	1	6,000 psi	NVA5002	3/4" Male x		6,000 psi	NVA500
1/2" Female		10,000 psi	NVA6002	1/2" Female		10,000 psi	NVA600
3/4" Female x	1	6,000 psi	NVA5025	3/4" Female x		6,000 psi	NVA502
3/4" Female		10.000 psi	NVA6025	3/4" Female		10,000 psi	NVA602
3/4" Male x	-	6,000 psi	NVA5005	3/4" Male x		6,000 psi	NVA500
3/4" Female		10,000 psi	NVA6005	3/4" Female		10,000 psi	NVA600
1" Female x	-	6,000 psi	NVA5023	1" Female x		6,000 psi	NVA502
1" Female		10,000 psi	NVA6023	1" Female		10,000 psi	NVA602
1" Male x	-	6,000 psi	NVA5003	1" Male x		6,000 psi	NVA500
1" Female		10,000 psi	NVA6003	1" Female		10,000 psi	NVA600
1/4" Female x		6,000 psi	NVA2020	1/4" Female x	Stainless Steel NACE	6,000 psi	NVA202
1/4" Female		10,000 psi	NVA3020	1/4" Female		10,000 psi	NVA302
1/4" Male x	-	6,000 psi	NVA2000	1/4" Male x		6,000 psi	NVA200
1/4" Female		10,000 psi	NVA3000	1/4" Female		10,000 psi	NVA300
3/8" Female x	-	6,000 psi	NVA2024	3/8" Female x		6,000 psi	NVA202
3/8" Female	Stainless Steel	10,000 psi	NVA3024	3/8" Female		10,000 psi	NVA302
3/8" Male x		6,000 psi	NVA2004	3/8" Male x		6,000 psi	NVA302
3/8" Female		10,000 psi	NVA3004	3/8" Female		10,000 psi	NVA300
1/2" Female x		6,000 psi	NVA2021	1/2" Female x		6,000 psi	NVA300
1/2" Female		10,000 psi	NVA3021	1/2" Female		10,000 psi	NVA202 NVA302
1/2" Male x		6,000 psi	NVA3021 NVA2001	1/2" Male x		6,000 psi	NVA302 NVA200
1/2" Female		10,000 psi	NVA2001 NVA3001	1/2 Male X 1/2" Female		10,000 psi	NVA200
3/4" Female x		6,000 psi	NVA2022	3/4" Female x		6,000 psi	NVA202
1/2" Female		10,000 psi	NVA2022 NVA3022	1/2" Female		10,000 psi	NVA202 NVA302
3/4" Male x		6,000 psi	NVA3022 NVA2002	3/4" Male x		6,000 psi	NVA302 NVA200
1/2" Female		10,000 psi	NVA2002 NVA3002	1/2" Female		10,000 psi	NVA200
3/4" Female x	-	6,000 psi	NVA3002 NVA2025	3/4" Female x		6,000 psi	NVA300 NVA202
3/4 Female X 3/4" Female		10,000 psi	NVA2025 NVA3025	3/4" Female X 3/4" Female		10,000 psi	NVA202 NVA302
3/4" Male x	-	6,000 psi	NVA3025 NVA2005	3/4" Male x		6,000 psi	NVA302 NVA200
3/4" Male x 3/4" Female							
		10,000 psi	NVA3005	3/4" Female		10,000 psi	NVA300
1" Female x		6,000 psi	NVA2023	1" Female x		6,000 psi	NVA202
1" Female	-	10,000 psi	NVA3023	1" Female		10,000 psi	NVA302
1" Male x		6,000 psi	NVA2003	1" Male x		6,000 psi	NVA200
1" Female		10,000 psi	NVA3003	1" Female		10,000 psi	NVA300

CPM = Carbon steel panel mount kit


WINTERS INSTRUMENTS


SPM = Stainless steel panel mount kit

Material


Description	Component Number	Carbon Steel	Carbon Steel NACE	Stainless Steel	Stainless Steel NACE
Body	1	Carbon Steel	Carbon Steel	316 SS	316 SS NACE
Bonnet	2	Carbon Steel	Carbon Steel	316 SS	316 SS NACE
Adapter Locknut	3	Carbon Steel	Carbon Steel	304 SS	304 SS
Adapter	4	316 SS	316 SS NACE	316 SS	316 SS NACE
Dustcap	5	Nylon	Nylon	Nylon	Nylon
Handle	6	Carbon Steel	Carbon Steel	304 SS	304 SS
Screw	7	304 SS	304 SS	304 SS	304 SS
Fastening Screw	8	304 SS	304 SS	304 SS	304 SS
Needle / Needle Tip	9	316 SS	316 SS NACE	316 SS	316 SS NACE
Gland Washer	10	Carbon Steel	Carbon Steel	304 SS	304 SS
Gland Packing	11	PTFE/Graphite	PTFE/Graphite	PTFE/Graphite	PTFE/Graphite
Dwell Pin	12	Carbon Steel	Carbon Steel	304 SS	304 SS
Gland Packing	13	PTFE/Graphite	PTFE/Graphite	PTFE/Graphite	PTFE/Graphite

Female x Female







Panel Mont Kit (CPM/SPM)



Male x Female





Dimensions

Dimensions						
Size	н	L	SQ			
1/4" Female x 1/4" Female	2.56" (65mm)	3.50" (89mm)	1.10" (28mm)			
1/4" Male x 1/4" Female	2.56" (65mm)	3.50" (89mm)	1.10" (28mm)			
3/8" Female x 3/8" Female	2.56" (65mm)	3.50" (89mm)	1.10" (28mm)			
3/8" Male x 3/8" Female	2.56" (65mm)	3.50" (89mm)	1.10" (28mm)			
1/2" Female x 1/2" Female	2.76" (70mm)	3.50" (89mm)	1.10" (28mm)			
1/2" Male x 1/2" Female	2.76" (70mm)	3.50" (89mm)	1.10" (28mm)			
3/4" Female x 1/2" Female	2.83" (72mm)	3.66" (93mm)	1.26" (32mm)			
3/4" Male x 1/2" Female	2.83" (72mm)	3.50" (89mm)	1.10" (28mm)			
3/4" Female x 3/4" Female	2.83" (72mm)	3.66" (93mm)	1.26" (32mm)			
3/4" Male x 3/4" Female	2.83" (72mm)	3.66" (93mm)	1.26" (32mm)			
1" Female x 1" Female	3.23" (82mm)	3.98" (101mm)	1.58" (40mm)			
1" Male x 1" Female	3.23" (82mm)	3.98" (101mm)	1.58" (40mm)			