

CONTRACT MATT

Professional quality, high opacity, quick drying matt emulsion for both old and new surface areas. A great combination of quality and value for money.

PERFORMANCE ADVANTAGES

- > High opacity - excellent coverage
- > Quick drying
- > Ideal for new plaster
- > Water-based
- > Economical



USES

- > Can be Brush, Roller or Spray applied.
- > To be used on plastered and embossed wall coverings, wallboards, concrete, cement rendering, brickwork and blockwork.
- > **FOR INTERIOR USE ONLY.**
- > Not suitable for areas subjected to heavy condensation.
- > **Do not apply when the air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.**

COLOUR RANGE

- > White or Magnolia. When using more than one tin of colour in the same room intermix before use.



FINISH

- > Matt.

PACK SIZE

- > Available in 5 and 15 Litre containers.

SPREADING RATE

- > Up to 13 square metres/litre per coat depending on the nature and porosity of the surface being painted.

DRYING TIME

- > Under normal drying, touch dry in 2 hours, recoatable after 4 hours.
- > Allow for adequate ventilation during the drying period.

SHELF LIFE

- > Up to 12 months if stored correctly in an unopened container.

PREPARATION

- > All surfaces must be painted should be clean, dry and free from loose and flaking material.
- > Prime bare surfaces with the appropriate Britannia Primer.
- > Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly.
- > Avoid the inhalation of dust.
- > Wear a suitable face mask if dry sanding.
- > Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.
- > For further information contact our Technical Sales Line on 01606 834015.

APPLICATION

- > **STIR WELL BEFORE USE.**
- > Easy to apply by brush or roller.
- > Also suitable for application by spray (see below).
- > If more than one can of colour is to be used in the same area, intermix before use.
- > Ensure good ventilation during application and drying.
- > Do not apply in temperatures below 10°C or in damp conditions.

SPRAY & THINNING APPLICATION

- > **Thinning:** sealing new or bare surfaces: up to 1.5 part clean water to 10 parts paint @ 2500 PSI / 172 bar with a 517 tip.

AIRLESS SPRAY:

- > **Un-thinned:** Spray @ 3000 PSI / 207 bar with 517 tip.
- > **Thinned:** 1 part clean water to 10 parts paint spray @ 2500 PSI / 172 bar with 517 tip.

CLEANING

- > Remove as much product as possible from application equipment before cleaning.
- > Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly.
- > Some local authorities have special facilities for the disposal of waste coatings.
- > Do not empty product into drains or watercourses.

PRECAUTIONS

- > Keep out of reach of children.
- > In case of contact with eyes wash immediately with plenty of water.
- > Remove splashes from skin with soap and water or a recognised hand cleaner.
- > Protect from freezing.
- > Do not apply paint if there is a risk of heavy rain or frost.
- > Do not use near fishponds.

HEALTH AND SAFETY

- > Please refer to the Safety, Health and Environmental Information on the container.
- > Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead.
- > For further information contact the Customer Relations Team.
- > When preparing the surfaces avoid the inhalation of dust and/or metal particles.
- > Wear a suitable facemask.
- > Material Safety Data Sheets for this and all other Britannia Paints products are freely available from the place of purchase or the address below.
- > Store in secure dry conditions inaccessible to children or animals.
- > Containers should be kept closed during storage.
- > Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

- > Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting.
- > Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.
- > Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate.
- > Britannia Paints are unable to guarantee results as it has no control over the conditions under which its products are applied.
- > For help or more information contact the Customer Relations Team on 01606 834015.
- > Before using this product please ensure you have the latest information.
- > The information is correct at date of issue January 2020.



Certificate Number 8516
ISO 9001



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 3 / May 2020