

# HEAVY DUTY MATT EMULSION

**Professional quality, smooth matt emulsion providing a durable and wipeable finish for interior walls and ceilings**

## PERFORMANCE ADVANTAGES

- > Smooth matt emulsion
- > Durable and wipeable finish
- > Excellent opacity
- > Water-based
- > One coat



## USES

- > Can be Brush, Roller or Spray applied.
- > Suitable for wall and ceiling surfaces in most normal interior situations. Ideal for use in schools, hotels, restaurants, canteens and bakeries where its low odour qualities combined with speed of drying enables work to be completed with minimum disruption.
- > **FOR INTERIOR USE ONLY.**
- > Not suitable for areas subjected to heavy condensation.
- > **Do not apply when the air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.**

## COLOUR RANGE

- > Brilliant White or Magnolia.
- > When using more than one tin of colour in the same room, intermix before use.

## FINISH

- > Matt.

## PACK SIZE

- > Available in 5 and 15 Litre containers.

## SPREADING RATE

- > Up to 15 square metres/litre per coat depending on the nature and porosity of the surface.
- > Strong or contrasting colours may require additional coats.
- > When using more than one tin of colour in the same room, intermix before use.

## DRYING TIME

- > Touch dry in 1-2 hours.
- > Recoatable after 2-4 hours.

## SHELF LIFE

- > Up to 12 months if stored correctly in an unopened container.



## PREPARATION

- > All surfaces must be painted should be clean, dry and free from loose and flaking material.
- > Prime bare surfaces with the appropriate Britannia Primer.
- > Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly.
- > Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.
- > Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.
- > For further information contact our Technical Sales Line on 01606 834015.

## APPLICATION

- > **STIR WELL BEFORE USE.**
- > Easy to apply by brush or roller.
- > Also suitable for application by spray (see below).
- > If more than one can of colour is to be used in the same area, intermix before use.
- > Ensure good ventilation during application and drying.
- > Do not apply in temperatures below 10°C or in damp conditions.

## SPRAY & THINNING APPLICATION

### AIRLESS SPRAY:

- > **Un-thinned:** Spray @ 3000 PSI / 207 bar with 517 tip.
- > **Thinned:** 1 part clean water to 10 parts paint spray @ 2500 PSI /172 bar with 517 tip.

## CLEANING

- > Remove as much product as possible from application equipment before cleaning.
- > Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly.
- > Some local authorities have special facilities for the disposal of waste coatings.
- > Do not empty product into drains or watercourses.

## PRECAUTIONS

- > Keep out of reach of children.
- > In case of contact with eyes wash immediately with plenty of water.
- > Remove splashes from skin with soap and water or a recognised hand cleaner.
- > Protect from freezing.
- > Do not apply paint if there is a risk of heavy rain or frost.
- > Do not use near fishponds.

## HEALTH AND SAFETY

- > Please refer to the Safety, Health and Environmental Information on the container.
- > Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead.
- > For further information contact the Britannia Sales Line on 01606 834015.
- > When preparing the surfaces avoid the inhalation of dust and/or metal particles.
- > Wear a suitable facemask. Material Safety Data Sheets for this and all other Britannia Paints products are freely available from the place of purchase or the address below.
- > Store in secure dry conditions inaccessible to children or animals.
- > Containers should be kept closed during storage.
- > Do not empty into drains, watercourses or access routes to septic tanks.

## GENERAL INFORMATION

- > Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting.
- > Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.
- > Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate.
- > Britannia Paints are unable to guarantee results as it has no control over the conditions under which its products are applied.
- > For help or more information contact the Customer Relations Team on 01606 834015.
- > Before using this product please ensure you have the latest information.
- > The information is correct at date of issue January 2020.



Certificate Number 8516  
ISO 9001



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF  
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 3 / May 2020