

# MULTI PATCH REPAIR

## RAPID REPAIR OF CONCRETE SURFACES INDOOR AND OUTDOOR

### PERFORMANCE ADVANTAGES

- > Fast setting cement based repair product
- > Just add water
- > Can be trafficked in as little as 2 hours subject to ambient temperature
- > Application up to 100mm in a single application
- > Fibre reinforced for added strength
- > Can be feather edged
- > Easy mix and application
- > Produces a concrete strength finish that can be painted



### USES

For use on interior and exterior concrete surfaces to repair surface damage. Can be used on ramps, steps, factory, warehouse and garage floors.

### WE DON'T RECOMMEND

- > Not recommended for use less than 5°C
- > Do not use for repairs greater than 100mm in a single application. Build up using multiple applications with 12 hours drying between applications.

### COLOUR RANGE

- > Light/Mid Grey concrete colour (can be coloured with suitable concrete pigment or overpainted).

### PACK SIZE

- > 10kg bag in a plastic bucket.

### COVERAGE

- > 10kg covers ~0.5m<sup>2</sup> at 10mm thick.

### DRYING (10°C)

- > Initial set after ~10 minutes.
- > Traffic after 2 hours depending on ambient temperature.
- > Can be painted after 12 hours depending on ambient temperature. Lower temperatures extend drying time.

### SHELF LIFE

- > 12 months in unopened containers from date of manufacture.
- > Keep in dry conditions.





## SURFACE PREPARATION

All surfaces should be clean, dry, free from dust, dirt, grease and oil contamination.

Remove any loose material and wire brush the surface. Apply at a minimal depth of 5mm for heavily trafficked areas.

Can be applied to damp concrete surfaces.

If in doubt always test a small area prior to use.

## MIXING

- > Remove the bag of powder and use bucket for mixing.
- > Mix 1 part water to 3 parts powder by volume.
- > Add water into bucket and add powder whilst mixing using a wooden mixing batten or drill mixer to obtain a pourable lump free blend.
- > **Only mix sufficient material that you can use within 10 minutes.**

## APPLICATION

- > Pour mixed product into repair and it will self level. It may require minimal use of a trowel on some occasions.
- > Typically applied at 5 -100mm depth and can be feather edged for lighter traffic applications.

## CLEANING

- > Clean all tools with water immediately after use.

## PRECAUTIONS

- > Always read label and Safety Data Sheet before use.
- > Wear gloves, goggles and suitable protective clothing.
- > In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- > Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water.
- > Keep out of reach of children.
- > Do not empty into drains.

## SAFETY

- > Good working practice should be followed.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

*As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.*

**If in doubt regarding any of the above points, please contact our technical services department for advice.**

**A Material Safety Data Sheet is available on request.**

*It is the users responsibility to ensure that this data sheet is current prior to using the product.*



Certificate Number 8516  
ISO 9001



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF  
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 1 / May 2021