

CellFlow Pro Series

Commercial-grade filtration at pin-drop noise level



Product specifications

	Pro600	Pro900			
Dimensions	50 x 54 x 18 cm	n 61x61x21cm			
Weight	10.9 kg	13.5 kg			
Room size*	45-125 m ²	80-200 m ²			
Efficiency rate**	CADR 14/W	CADR 20/W			
Mounting	Ceiling or floor				
Remote control	Yes				
Color	White				
Filter	EcoPrecision™long-life filter				
Degree of filtration**	H14 level PM0,1 99,99% and PM0,3 99,99%				
CCM capacity over time***	Top-rating P4				
Filter exchange interval	18 months				
Motor	Brushless AC-motor with HyBlade ^R technology from ebmpapst GmbH				

Key efficiency data

Fan speed	CADR*** smoke		Noise dB (A)		Energy (W)	
	Pro600	Pro900	Pro600	Pro900	Pro600	Pro900
1	135	300	21	23	12	15
2 (daily use)	350	450	29	31	25	25
3	600	950	44	49	45	70

* based on 5-2 air changes per hour.

- ** as certified by Intertek Group according to standard ANSI/AHAM AC-1-2015.
- *** Industry leading 98% remaining CADR, tested according to ind. Std GB/T 18801-2015. (CCM acronym for Cumulative Clean Mass)

Industry leadership

- Running costs
- Purification efficiency
- Noise levels





Efficient filtration of


Microbes

Bacteria Viruses Mold

Other pollutants

Ultra-fine dust Traffic pollution Pollen Printer particles Smoke Industrial pollution Pet allergens

CellFlow patented technology





LightAir

Watch video on how the CellFlow technology works.

www.lightair.com/professional