



ARRIVING SPRING 2024

# THE TERRAIN ATTACK R/T

Designed for the true off-road enthusiast, the Terrain Attack R/T is engineered to conquer the toughest terrains with ease, delivering exceptional performance and durability, without compromising on-road comfort.

## 2 SIDEWALL DESIGNS. SAME OPTIMAL PERFORMANCE.

The Terrain Attack R/T features two unique sidewall designs, allowing for further vehicle customization.

### SIDEWALL 1

A rugged, pocketed block design with varying heights combines style and exceptional off-road performance.

### SIDEWALL 2

A dynamic stepped V-pattern, along with integrated Amp "A" tread blocks, generates numerous gripping edges along the sidewall.



50K MILE  
TREAD LIFE  
WARRANTY



MANUFACTURERS  
LIMITED  
LIFETIME  
WARRANTY

#CONTROLEVERYTERRAIN



## WHAT MAKES THE TERRAIN ATTACK R/T SUPERIOR?



### OFF-ROAD TRACTION

Stone ejectors channel away water, mud, rocks, & other debris to maintain maximum grip and performance.



### ALL-SEASON PERFORMANCE

Large, open shoulder blocks greatly improve off-road traction and enhance grip in extreme weather conditions.



### LONG-LASTING DURABILITY

Staggered sidewall provides protection against punctures and abrasions in harsh environments.



### WIDE CONTACT CENTER PATCH

AMP Tires' hybrid tread pattern is designed with versatility in mind. The wide contact center patch increases surface coverage on any terrain, while providing longer tread life and a quiet and smooth ride on the road.



### VARIABLE PITCH TREAD PATTERN

Innovative tread design optimizes road contact, reduces road noise, and enhances overall performance.

## PRODUCT SPECIFICATIONS

| TIRE SIZE     | PART NO.         | LOAD RANGE | TREAD DEPTH (1/32") | OVERALL DIAMETER (IN) | OVERALL WIDTH (IN) | MAX LOAD SINGLE | MAX PRESS. SINGLE | APPROVED RIM WIDTH RANGE (IN) |
|---------------|------------------|------------|---------------------|-----------------------|--------------------|-----------------|-------------------|-------------------------------|
| 17"           |                  |            |                     |                       |                    |                 |                   |                               |
| LT285/70R17   | 285-7017AMP/RTC  | C          | 13.0                | 32.8                  | 11.5               | 2755/2535LBS    | 50PSI             | 7.5-9.5 (8.5)                 |
| P265/70R17    | 265-7017AMP/RTSL | SL         | 11.1                | 31.7                  | 10.7               | 2535LBS         | 44PSI             | 7.0-9.0 (8.0)                 |
| 35X12.50R17LT | 35-125017AMP/RTE | E          | 15.0                | 34.8                  | 12.5               | 3640LBS         | 65PSI             | 8.0-10.5 (10.0)               |
| 20"           |                  |            |                     |                       |                    |                 |                   |                               |
| LT285/55R20   | 285-5520AMP/RTE  | E          | 13.0                | 32.6                  | 11.7               | 3305/3000LBS    | 80PSI             | 8.5-10.0 (9.0)                |
| 35X12.50R20LT | 35-125020AMP/RTF | F          | 15.0                | 34.8                  | 12.5               | 3640LBS         | 80PSI             | 8.5-11.0 (10.0)               |
| 35X12.50R20LT | 35-125020AMP/RTE | E          | 15.0                | 34.8                  | 12.5               | 3195LBS         | 65PSI             | 8.5-11.0 (10.0)               |
| 33X12.50R20LT | 33-125020AMP/RTE | E          | 15.0                | 32.8                  | 12.5               | 2600LBS         | 65PSI             | 8.5-11.0 (10.0)               |
| LT305/55R20   | 305-5520AMP/RTF  | F          | 13.0                | 33.5                  | 12.4               | 3640/3305BS     | 80PSI             | 9.0-11.0 (9.5)                |
| 22"           |                  |            |                     |                       |                    |                 |                   |                               |
| 35X12.50R22LT | 35-125022AMP/RTF | F          | 15.0                | 34.8                  | 12.5               | 3195LBS         | 80PSI             | 8.5-11.0 (10.0)               |
| 35X12.50R22LT | 35-125022AMP/RTE | E          | 15.0                | 34.8                  | 12.5               | 2835LBS         | 65PSI             | 8.5-11.0 (10.0)               |
| 33X12.50R22LT | 33-125022AMP/RTF | F          | 15.0                | 32.8                  | 12.5               | 2600LBS         | 80PSI             | 8.5-11.0 (10.0)               |
| 33X12.50R22LT | 33-125022AMP/RTE | E          | 15.0                | 32.8                  | 12.5               | 2270LBS         | 65PSI             | 8.5-11.0 (10.0)               |
| 24"           |                  |            |                     |                       |                    |                 |                   |                               |
| 35X13.50R24LT | 35-135024AMP/RTF | F          | 15.0                | 34.8                  | 13.4               | 2755LBS         | 80PSI             | 11.5-13.5 (12.0)              |
| 35X13.50R24LT | 35-135024AMP/RTE | E          | 15.0                | 34.8                  | 13.4               | 2470LBS         | 65PSI             | 11.5-13.5 (12.0)              |
| 37X13.50R24LT | 37-135024AMP/RTF | F          | 15.0                | 36.8                  | 13.6               | 3525LBS         | 80PSI             | 9.5-12.0 (11.0)               |
| 37X13.50R24LT | 37-135024AMP/RTE | E          | 15.0                | 36.8                  | 13.6               | 3085LBS         | 65PSI             | 9.5-12.0 (11.0)               |

FULLY TESTED WINTER TIRE



# TERRAIN ATTACK A/T A

With an off-road attitude and smooth on-road characteristics, the AMP Terrain Attack A/T is the ultimate adventure tire. The performance tread design features a multi-block pattern that delivers stable control in a wide variety of environments and terrain. Equipped with a large selection of sizing and a 40,000 mi tread lifewarranty, let the Terrain Attack take you on every journey.



## PERFORMANCE RATINGS



DRY SURFACE



WET SURFACE



RIDE COMFORT



TREAD LIFE



OFF-ROAD  
PERFORMANCE



### PERFORMANCE TREAD DESIGN

Unique multi-block tread design ensures smooth ride quality along with superior off road handling and grip.



### TWIN-LUG SIDEWALL

Sidewall designed with dual variation lug technology for greatly improved traction in all environments and weather conditions.



### OFF-ROAD PERFORMANCE

The staggered tread block design was made to improve traction in loose dirt, debris and sand.



### STAGGERED TREAD DEPTH

Deep, stepped tread blocks channel dirt, mud, snow, slush and water away from the tire in all weather conditions.



## PRODUCT SPECIFICATIONS

| TIRE SIZE     | PART NO.         | LOAD RANGE | TREAD DEPTH (1/32") | OVERALL DIAMETER (IN) | OVERALL WIDTH (IN) | MAX LOAD SINGLE | MAX PRESS. SINGLE | APPROVED RIM WIDTH RANGE (IN) |
|---------------|------------------|------------|---------------------|-----------------------|--------------------|-----------------|-------------------|-------------------------------|
| <b>17"</b>    |                  |            |                     |                       |                    |                 |                   |                               |
| LT265/70R17   | 265-7017AMP/CA3  | E          | 15.5                | 31.7                  | 10.7               | 3195LBS/2910LBS | 80PSI             | 7.0-9                         |
| LT285/70R17   | 285-7017AMP/CA3  | E          | 15.5                | 32.8                  | 11.5               | 3195LBS/2910LBS | 80PSI             | 7.5-9.5                       |
| LT315/70R17   | 315-7017AMP/CA3  | E          | 15.5                | 34.4                  | 12.7               | 3195LBS/2910LBS | 65PSI             | 8.0-10.5                      |
| <b>18"</b>    |                  |            |                     |                       |                    |                 |                   |                               |
| LT305/60R18   | 305-6018AMP/CA3  | E          | 15.5                | 32.4                  | 12.2               | 3195LBS/2910LBS | 65PSI             | 9.0-11.0                      |
| LT305/70R18   | 305-7018AMP/CA3  | E          | 15.5                | 34.8                  | 12.2               | 3750LBS/3415LBS | 65PSI             | 8.0-10.0                      |
| <b>20"</b>    |                  |            |                     |                       |                    |                 |                   |                               |
| LT265/50R20   | 265-5020AMP/CA3  | E          | 15.5                | 30.5                  | 10.9               | 2680LBS/2470LBS | 80PSI             | 8.0-9.5                       |
| LT275/55R20   | 275-5520AMP/CA3  | D          | 15.5                | 31.9                  | 11.2               | 2680LBS/2470LBS | 65PSI             | 8.0-9.5                       |
| LT285/55R20   | 285-5520AMP/CA3  | E          | 15.5                | 32.4                  | 11.7               | 3305LBS/3000LBS | 80PSI             | 8.0-10.0                      |
| LT305/55R20   | 305-5520AMP/CA3  | E          | 15.5                | 33.2                  | 12.4               | 3195LBS/2910LBS | 65PSI             | 9.0-11.0                      |
| 35x12.50R20LT | 35-125020AMP/CA3 | E          | 15.5                | 34.5                  | 12.5               | 3195LBS         | 65PSI             | 8.5-11.0                      |
| 37x12.50R20LT | 37-125020AMP/CA3 | E          | 15.5                | 36.5                  | 12.5               | 3750LBS         | 65PSI             | 8.5-11.0                      |
| <b>22"</b>    |                  |            |                     |                       |                    |                 |                   |                               |
| 305/40R22     | 305-4022AMP/CA3  | XL         | 13.9                | 31.6                  | 12.3               | 2601LBS         | 50PSI             | 10.0-12.0                     |
| 33x12.50R22LT | 33-125022AMP/CA3 | E          | 15.5                | 32.5                  | 12.5               | 2270LBS         | 65PSI             | 8.5-11.0                      |
| 35x12.50R22LT | 35-125022AMP/CA3 | E          | 15.5                | 34.5                  | 12.5               | 2835LBS         | 65PSI             | 8.5-11.0                      |

FULLY TESTED WINTER TIRE



# TERRAIN ATTACK A/T P

The all-new AMP Terrain Pro A/T delivers a longer tread life and withstands demanding environments. With deep, multi-function tread grooves it provides enhanced traction in a wide variety of conditions while delivering a smooth and controlled ride. With a broad selection of sizing and a 60,000 mi tread life warranty, drive the Terrain Pro A/T to be the leader of the pack.

## PERFORMANCE RATINGS



DRY SURFACE



WET SURFACE



RIDE COMFORT



TREAD LIFE



OFF-ROAD  
PERFORMANCE



### PERFORMANCE TREAD DESIGN

Stepped tread blocks allow more stable control and multidirectional sipes create greater traction in snow.



### OFF-ROAD PERFORMANCE

Advanced compound prevents chipping and delivers a longer tread life with more consistent contact surface to deliver a smooth and controlled ride.



### STEEP TREAD DEPTH

Deep grooves and rock ejectors keep tread grooves free of mud, snow, dirt and gravel while mitigating possible punctures.



### TWIN-LUG SIDEWALL

Unique "twin peaks" sidewall and open shoulder design deliver assertive performance in every condition and help evacuate water, mud and snow for improved traction.



## PRODUCT SPECIFICATIONS

| TIRE SIZE     | PART NO.          | LOAD RANGE | TREAD DEPTH (1/32") | OVERALL DIAMETER (IN) | OVERALL WIDTH (IN) | MAX LOAD SINGLE  | MAX PRESS. SINGLE | APPROVED RIM WIDTH RANGE (IN) |
|---------------|-------------------|------------|---------------------|-----------------------|--------------------|------------------|-------------------|-------------------------------|
| 16"           |                   |            |                     |                       |                    |                  |                   |                               |
| LT285/75R16   | 285-7516AMP/CA2   | E          | 15.1                | 32.8                  | 11.3               | 3750LBS/3415LBS  | 80PSI             | 7.5-9.5                       |
| 17"           |                   |            |                     |                       |                    |                  |                   |                               |
| LT265/70R17   | 265-7017AMP/CA2   | E          | 15.1                | 31.7                  | 10.7               | 3195LBS/2910LBS  | 80PSI             | 7.0-9.0                       |
| LT285/70R17   | 285-7017AMP/CA2   | E          | 15.1                | 32.8                  | 11.5               | 3195LBS/2910LBS  | 80PSI             | 7.5-9.5                       |
| LT315/70R17   | 315-7017AMP/CA2   | E          | 15.1                | 34.4                  | 12.7               | 3195LBS/2910LBS  | 65PSI             | 8.0-10.5                      |
| 18"           |                   |            |                     |                       |                    |                  |                   |                               |
| LT275/70R18   | 275-7018AMP/CA2   | E          | 15.8                | 33.2                  | 11.0               | 3640LBS/3305LBS  | 80PSI             | 7.0-9.0                       |
| LT285/65R18   | 285-6518AMP/CA2   | E          | 15.8                | 32.6                  | 11.5               | 3640LBS/3305LBS  | 80PSI             | 8.5-10.0                      |
| LT325/65R18   | 325-6518AMP/CA2   | E          | 15.8                | 34.6                  | 13.0               | 3860LBS/3525 LBS | 65PSI             | 9.5-11.5                      |
| 20"           |                   |            |                     |                       |                    |                  |                   |                               |
| LT265/60R20   | 265-6020AMP/CA2   | E          | 15.1                | 32.5                  | 10.7               | 3195LBS/2910LBS  | 80PSI             | 8.0-9.5                       |
| LT275/55R20   | 275-5520AMP/CA2   | D          | 15.8                | 31.9                  | 11.2               | 2680LBS/2470LBS  | 65PSI             | 8.0-9.5                       |
| LT275/60R20   | 275-6020AMP/CA2   | E          | 15.8                | 33.0                  | 11.0               | 3415LBS/3085LBS  | 80PSI             | 8.0-9.5                       |
| LT275/65R20   | 275-6520AMP/CA2   | E          | 15.1                | 34.1                  | 11.0               | 3750LBS/3415LBS  | 80PSI             | 8.0-9.5                       |
| LT285/55R20   | 285-5520AMP/CA2   | E          | 15.8                | 32.4                  | 11.7               | 3305LBS/3000LBS  | 80PSI             | 8.5-10.0                      |
| LT285/60R20   | 285-6020AMP/CA2   | E          | 15.1                | 33.5                  | 11.5               | 3640LBS/3305LBS  | 80PSI             | 8.5-10.0                      |
| LT295/65R20   | 295-6520AMP/CA2   | E          | 15.5                | 35.1                  | 11.8               | 4080LBS/3750LBS  | 80PSI             | 8.5-10.5                      |
| LT305/55R20   | 305-5520AMP/CA2   | E          | 15.8                | 33.2                  | 12.4               | 3195LBS/2910LBS  | 65PSI             | 9.0-11.0                      |
| 33X12.50R20LT | 33-125020AMP/CA2  | E          | 15.8                | 32.5                  | 12.5               | 2600LBS          | 65PSI             | 8.5-11.0                      |
| 35X12.50R20LT | 35-125020AMP/CA2  | E          | 15.5                | 34.5                  | 12.5               | 3195LBS          | 65PSI             | 8.5-11.0                      |
| LT325/60R20   | 325-6020AMP/CA2   | E          | 15.8                | 35.4                  | 13.0               | 3750LBS/3415LBS  | 65PSI             | 9.5-11.5                      |
| 22"           |                   |            |                     |                       |                    |                  |                   |                               |
| LT285/45R22   | 285-4522AMP/CA2   | D          | 15.8                | 32.1                  | 11.2               | 2835LBS          | 65PSI             | 9.0-10.5                      |
| LT285/55R22   | 285-5522AMP/CA2   | E          | 15.5                | 34.4                  | 11.7               | 3525LBS/3195LBS  | 80PSI             | 8.5-10.0                      |
| LT295/50R22   | 295-5022AMP/CA2   | E          | 15.8                | 33.7                  | 12.2               | 3305LBS/3000LBS  | 80PSI             | 8.5-10.5                      |
| 24"           |                   |            |                     |                       |                    |                  |                   |                               |
| P305/35R24    | 305-3524AMP/CA2   | XL         | 14.4                | 32.5                  | 12.2               | 2469LBS          | 50PSI             | 10.0-12.0                     |
| 33x12.50R24LT | 33-125024AMP/CA2F | F          | 15.8                | 32.5                  | 12.6               | 2095LBS          | 80PSI             | 10.5-12.5                     |
| 35X12.50R24LT | 35-125024AMP/CA2F | F          | 15.8                | 34.5                  | 12.5               | 2755LBS          | 80PSI             | 10.0-12.0                     |

# MUD TERRAIN ATTACK M/T A

The AMP Terrain Attack M/T is designed to perform in the most extreme conditions while offering improved grip and handling for better on-road performance. The 3-ply "A" logo sidewall provides biting edges and outstanding grip in mud, rock, sand, snow and more. A full range of sizes up to 38 inches tall, the Terrain Attack M/T will conquer anything in its path.



## PERFORMANCE RATINGS



DRY SURFACE



WET SURFACE



RIDE COMFORT



TREAD LIFE



OFF-ROAD  
PERFORMANCE



### PERFORMANCE TREAD DESIGN

The deep sipes and distinct channel design significantly increase traction in wet conditions.



### OFF-ROAD PERFORMANCE

The unique shoulder design features a staggered tread block that provides reliable grip in unreliable terrain and consistent traction for better on road performance.



### AGGRESSIVE TREAD

The tread pattern is aggressively designed to remove mud, dirt, snow and debris while keeping continuous contact for superior off road traction and better on-road control.



### TWIN-LUG SIDEWALL

Reinforced sidewall boasts "A" logo lug design which provides dynamic biting edges to maintain grip through the most extreme conditions or when airing down tires.



## PRODUCT SPECIFICATIONS

| TIRE SIZE     | PART NO.          | LOAD RANGE | TREAD DEPTH (1/32") | OVERALL DIAMETER (IN) | OVERALL WIDTH (IN) | MAX LOAD SINGLE | MAX PRESS. SINGLE | APPROVED RIM WIDTH RANGE (IN) |
|---------------|-------------------|------------|---------------------|-----------------------|--------------------|-----------------|-------------------|-------------------------------|
| <b>17"</b>    |                   |            |                     |                       |                    |                 |                   |                               |
| 35x12.50R17LT | 35-125017AMP/CM2  | E          | 19.0                | 34.8                  | 12.5               | 3195LBS         | 65PSI             | 8.5-11.0                      |
| 37x12.50R17LT | 37-125017AMP/CM2  | D          | 19.0                | 36.8                  | 12.5               | 3525LBS         | 50PSI             | 9.0-10.5                      |
| <b>18"</b>    |                   |            |                     |                       |                    |                 |                   |                               |
| LT285/65R18   | 285-6518AMP/CM2   | E          | 19.0                | 32.8                  | 11.5               | 3640LBS/3305LBS | 80PSI             | 8.5-10.0                      |
| 35x12.50R18LT | 35-125018AMP/CM2  | E          | 19.0                | 34.8                  | 12.5               | 3415LBS         | 65PSI             | 8.5-11.0                      |
| <b>20"</b>    |                   |            |                     |                       |                    |                 |                   |                               |
| LT285/55R20   | 285-5520AMP/CM2   | E          | 19.0                | 32.6                  | 11.7               | 3305/3000LBS    | 80PSI             | 8.0-10.0                      |
| LT305/55R20   | 305-5520AMP/CM2   | E          | 19.0                | 33.5                  | 12.4               | 3195LBS/2910LBS | 65PSI             | 9.0-11.0                      |
| 33x12.50R20LT | 33-125020AMP/CM2  | E          | 19.0                | 32.8                  | 12.5               | 2600LBS         | 65PSI             | 8.5-11.0                      |
| 35X11.50R20LT | 35-115020AMP/CM2  | E          | 19.5                | 34.8                  | 11.4               | 3525LBS         | 80PSI             | 8.0-10                        |
| 35x12.50R20LT | 35-125020AMP/CM2  | E          | 19.0                | 34.8                  | 12.5               | 3195LBS         | 65PSI             | 8.5-11.0                      |
| 37x13.50R20LT | 37-135020AMP/CM2  | E          | 19.0                | 36.8                  | 13.6               | 3860LBS         | 65PSI             | 9.5-12.0                      |
| <b>22"</b>    |                   |            |                     |                       |                    |                 |                   |                               |
| LT325/50R22   | 325-5022AMP/CM2   | E          | 19.0                | 34.8                  | 13.2               | 3305LBS         | 65PSI             | 9.5-11.5                      |
| 33x12.50R22LT | 33-125022AMP/CM2  | E          | 19.0                | 32.5                  | 12.5               | 2270LBS         | 65PSI             | 8.5-11.0                      |
| 33x14.50R22LT | 33-145022AMP/CM2F | F          | 19.0                | 32.7                  | 14.5               | 2830LBS         | 95PSI             | 10.0-13.0                     |
| 35x15.50R22LT | 35-155022AMP/CM2F | F          | 19.0                | 34.7                  | 15.5               | 3640LBS         | 80PSI             | 11.0-14.0                     |
| 37x12.50R22LT | 37-125022AMP/CM2F | F          | 19.5                | 36.8                  | 12.5               | 3860LBS         | 80PSI             | 8.5-11.0                      |
| 37x13.50R22LT | 37-135022AMP/CM2  | E          | 19.0                | 36.8                  | 13.6               | 3415LBS         | 65PSI             | 9.5-12.0                      |
| <b>24"</b>    |                   |            |                     |                       |                    |                 |                   |                               |
| 33x13.50R24LT | 33-135024AMP/CM2F | F          | 19.5                | 32.5                  | 13.6               | 3200LBS         | 80PSI             | 9.5-12.0                      |
| 38x13.50R24LT | 35-135024AMP/CM2  | E          | 19.5                | 34.8                  | 13.4               | 2470LBS         | 65PSI             | 9.5-12.0                      |
| 35x13.50R24LT | 35-155024AMP/CM2  | E          | 19.5                | 34.8                  | 15.3               | 2835LBS         | 65PSI             | 12.5-15                       |
| 35X15.50R24LT | 37-135024AMP/CM2  | E          | 21.0                | 36.8                  | 13.6               | 3085LBS         | 65PSI             | 9.5-12.0                      |
| 37x13.50R24LT | 38-155024AMP/CM2  | E          | 19.5                | 37.8                  | 15.5               | 3860LBS         | 65PSI             | 12.5-15                       |
| 38X15.50R24LT | 38-135024AMP/CM2F | F          | 19.5                | 37.8                  | 13.6               | 3860LBS         | 80PSI             | 9.5-12                        |
| <b>26"</b>    |                   |            |                     |                       |                    |                 |                   |                               |
| 33X13.50R26LT | 33-135026AMP/CM2F | F          | 19.5                | 32.8                  | 13.6               | 2755LBS         | 80PSI             | 12.5-15                       |
| 35x13.50R26LT | 35-135026AMP/CM2F | F          | 19.5                | 34.6                  | 13.6               | 2835LBS         | 80PSI             | 11 - 13                       |
| 37x13.50R26LT | 37-135026AMP/CM2F | F          | 19.5                | 36.3                  | 13.6               | 2835LBS         | 80PSI             | 11 - 13                       |
| 38X15.50R26LT | 38-155026AMP/CM2  | E          | 19.5                | 37.7                  | 15.2               | 3750LBS         | 65PSI             | 12.5-15                       |
| <b>28"</b>    |                   |            |                     |                       |                    |                 |                   |                               |
| 37X13.50R28LT | 37-135028AMP/CM2F | F          | 19.5                | 36.8                  | 13.6               | 2600LBS         | 80PSI             | 11-14                         |