

## Technical Data Sheet | CH-L5F2P16

### LithiumVault FirePro® Cabinet with Control Panel & Charging | Single-Phase

Cabinet designed for storing and charging lithium-ion batteries with fire safety features certified for 90-minutes of fire protection.

#### Product Characteristics

External Dimensions (WxDxH)	1200 x 600 x 2050mm
Internal Dimensions (WxDxH)	1095 x 446 x 1540mm
Shelf Dimensions (WxDxH)	1094 x 420 x 39mm
Number of Shelves	4 x perforated shelves
Doors	2
Door Locks	2 (4 x keys supplied)
Charging Points	24 (6 x power sockets per shelf)
Tare Weight	350kg (empty cabinets, excl. accessories)
Standard Colour	Black door with grey frame and interior
Socket Options	Type E, type F, type G
Power Socket	Standard Regional Socket
Cable Section	2m 3G2.5mm <sup>2</sup>
Max Amp Output	16A
Voltage	230V
Max Socket Power	3,680W
Max Total Power	3,680W



#### Product Features

- 90-Minutes Fire Rated.
- Steel Construction.
- Anti-spark hinges.
- Ventilation.
- Self-closing door system.
- 16A charging sockets with illuminated on/off safety switch.
- 3G2.5mm<sup>2</sup> cable section (Single phase).
- FirePro® fire detection and automatic extinguishing system with FPC-2V2 control panel.
- Sounder beacon.
- Smoke and heat sensors.
- LPCB Certified to EN 12094-1 and EN 54-2 and 4.
- Spill tray.

Colour, socket and power configurations will be reflected in product code