

Combination Store - CBS2

Backed by our 20 year structural guarantee*

The base is manufactured from 3mm mild steel sheet with RHS cross members and pressed ribs for additional strength. The main frame work is manufactured from rolled hollow section, while the back, sides and door panels are pressed from 2mm mild steel sheet corrugated where required. The roof is fitted with lifting eyes and fully welded around perimeter.

Each end of the unit is fitted with lockable, sliding doors giving access to drum/IBC store areas and the shelved walk-in store (in the middle) is accessed via a hinged door on the side of the unit. The internal divides between the different areas is an open framework and the entire unit is protected by a fully seam welded sump which fully complies with all the current UK regulations relating to sump capacities. The sumps in the walk-in section are covered by galvanised steel grid mesh with the drum/IBC storage areas covered with steel sump channels and placed directly onto a steel support frame. The drum/IBC storage can be fitted with grid mesh if requested. The underside of the unit is fitted with plinths to eliminate ground contact and reduce the risk of corrosion, prior to painting the unit is fully shot blasted to provide a clean and keyed surface.

This model can hold a total of 32 x 205ltr drums or 8 x 1000ltr IBC's across two levels and will accommodate standard 1200mm x 1200mm, 1200mm x 1000mm and 1200mm x 800mm pallets, plus the walk-in area which contains shelving for small containers.



Combination Store - CBS2

SPECIFICATION	
Configuration	FLT accessed store across one end with a walk-in store
External size	6000mm L x 3000mm W x 3325mm H at the highest point of the unit
Lower level clear space	1334mm H in the FLT accessed store
Upper level clear space	1350mm H in the FLT accessed store
Walk-in area internal size	3m x 3m
Nº of containers	32 x 205ltr or 8 x 1000ltr
Number of rack sets	2
Rack set size	1930mm L x 620mm W x 1800mm H (overall)
Number of shelves per rack set	2
Incremental adjustment for shelving	50mm
Load capacity per shelf	500kg
Sump capacity	4500ltr
Colour	Green RAL 6029
Tare weight	3000kg
Type of doors	4 sliding (2 per FLK accessed store) & 1 hinged
Type of door lock	Padlock points & keys lock + Cam-lock gear (Padlocks not supplied)
Access apertures	1360mm W x 2780mm H & 1250mm W x 2170mm H

Chargeable Options:

- Air vents
- Full dividing wall between the two compartments

Please notify us at the time of ordering if you require any of these options.

