

## Ceiling Mounted Emergency Showers - ABS Shower Head - CMS

Manufactured using galvanised pipe work which is protected with an anti-corrosive Polyamide 11 high visibility yellow plastic coating to give good resistance to acids, bases, seawater and oils, all fittings and elbow joints are brass and the 250mmØ shower head is manufactured from ABS reinforced plastic.

This ceiling mounted safety shower has been designed to meet and exceed the internationally recognised standards: EN15154 parts 1 & 2, DIN12899.3 and ANSI Z358.1.



### FEATURES

Water inlet	1" BSP
Water inlet pressure	Recommended 2 bar with a maximum of 8 bar - please notify us prior to ordering if your water pressure is below 1.5 bar
Water flow rate	Regulated at 110lpm
Operation	Pull handle
Water valve	Full bore 1"
Total weight	3kg
Dimensions	80 x 27 x 13cm

### EMPTEEZY LTD.

Muir Road Houstoun Industrial Estate Livingston EH54 5DR

**Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466**

e-mail: [sales@empteezy.co.uk](mailto:sales@empteezy.co.uk) | [www.empteezy.co.uk](http://www.empteezy.co.uk)

Registered in Scotland 100049