

CS3 - Chemstor[®] Walk-in Store

Backed by our 20 year structural guarantee*

A pressed steel welded body construction provides the structural strength for this unit, while the roof which is fitted with lifting eyes is manufactured from mild steel. The two easy glide sliding doors are constructed from mild steel and are fitted with a central lock and padlock points (padlocks not supplied).

Constructed from mild steel, the sump is fully seam welded and fitted with galvanised steel pallet channels and is as you would expect fully compliant with all current UK regulations relating to sump capacities and the underside is fitted with plinths to eliminate contact with ground and reduce the risk of corrosion. High and low level louvre vents complete with flame arrestor mesh are fitted as standard and the unit is fitted with 2 full length/half depth shelves and 1 full length, ¼ depth shelf at the top. Prior to painting the unit is fully shot blasted to provide a clean and keyed surface.

This model can hold up to 80 x 25ltr cans plus small containers on the top shelf.



SPECIFICATION	
External size	3000mm L x 1500mm W x 2403mm H at the highest point on the unit
No of containers	80 x 25ltr + 1ltr, 2.5ltr or 5ltr cans
Space between shelves	580mm from sump mesh to underside of lower shelf & lower shelf to underside of middle shelf. 320mm from middle shelf to underside of top small shelf and 260mm to the underside of the roof
Load capacity per shelf	400kg
Sump capacity	1125ltr
Colour	Green RAL 6029
Tare weight	1048kg
Type of doors	2 sliding
Access aperture	1371mm W x 1967mm H
Paint specification	A high build, quick drying primer/topcoat paint specifically designed for use directly on to metal or bare steel, this paint contains zinc phosphate anti-corrosive pigments and is applied with a minimum dry film thickness of 75 microns.

This unit will be delivered by an HGV, possibly articulated therefore please ensure that a vehicle of this type can access your premises before ordering and advise us accordingly. You will require an appropriate size/capacity fork lift truck to offload this item from the delivery vehicle. Our standard delivery doesn't include any offloading, but we do offer a chargeable HIAB service, which means the unit can be offloaded in any location that the HIAB vehicle can stand adjacent to. The use of this service doesn't include the levelling of the unit or any responsibility for where you ask for it to be placed on the ground. Any subsequent issues with subsidence or the unit becoming un-level remain your (the customers') responsibility.

The unit must be positioned on a solid level surface, ideally concrete of circa 150mm in depth and 100mm bigger overall than the unit. The purpose of this is to ensure the unit does not settle unevenly when loaded. Empteezy will not accept responsibility for the correction of units which have been settled on uneven or subsiding ground.

