

1 Hour Fire Rated Store - DPU16-4FR

16 drums or 4 IBC

Backed by our 20 year structural guarantee - details available on request

A rolled hollow welded frame creates a strong structure for this fire rated drum store. The walls, two hinged-doors and roof have been in-filled with Rockwool Firebatt insulation and covered with sheet steel to provide 1 hour fire rating.

A fully seam welded sump, with profiled rib straighteners and galvanised support channels, creates a bunded area in case of a spill, and base plinths eliminate contact with the ground. High and low level vents fitted with intumescent elements allow air to circulate, however in the event of a fire, these elements will expand and seal the vents, this takes place at temperatures above 150°C.

The sump fully complies with all the UK regulations relating to sump capacities.

Empteezy have tested the components used in our fire rated stores in conjunction with Bodycote Warrington Fire Consulting to ensure full compliance with BS EN 1634-1: 2000 (report certificate number 160129).

NOTE: The "floor" area above the sump is covered with galvanised steel channel sections so that pallets can be stored directly on to it, while the upper shelf is an open, box section construction designed to support pallets. Grid mesh shelving is available for the upper shelf as a chargeable option for those who wish to have it fitted with a full "floor". Grid mesh flooring is also available for both levels. Please contact us for further information.

SPECIFICATION	
External size	L3000 x W1500 x H3295mm at the highest point on the unit
Number of containers	Sixteen 205ltr drums or four 1000ltr IBCs
Sump capacity	1125ltr
Colour	Green RAL 6029
Tare weight	2250kg



EMPTEEZY LTD.

Muir Road Houston Industrial Estate Livingston EH54 5DR

Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466

e-mail: sales@empteezy.co.uk | www.empteezy.co.uk

Registered in Scotland 100049