

Drum Store - DPU32-8R

Backed by our 20 year structural guarantee*

This model is fitted with roller shutter doors to allow access to the entire unit at the same time. The fully seam welded mild steel sump, which fully complies with all the current UK regulations relating to sump capacities is fitted with galvanised steel pallet channels (3 per pallet space), while pallets on the upper level sit directly onto a steel support frame. The base which is fitted with plinths to keep it off the ground and reduce the risk of corrosion is manufactured from 3mm mild steel sheet with RHS cross members and pressed ribs.

All the corner posts, shelves, main rails and cross members are constructed from rolled hollow section and the back and sides are pressed from mild steel sheet, which is corrugated where required. The sloping roof is fitted with suitable bracing, is fully welded around perimeter and incorporates crane lifting points). Prior to painting the unit is fully shot blasted to provide a clean and keyed surface.

This model can hold up to 32 x 205ltr drums or 8 x 1000ltr IBC's across two levels and will accommodate standard 1200mm x 1200mm, 1200mm x 1000mm and 1200mm x 800mm pallets.

*Full details available on request



SPECIFICATION	
External size	5920mm L x 1500mm W x 3505mm H at the highest point of the unit
Lower level clear space	1335mm H
Upper level clear space	1425mm H
N ^o of containers	32 x 205ltr – vertical or 8 x 1000ltr
Sump capacity	2200ltr
Colour	Green RAL 6029
Tare weight	2000kg
Type of doors	2 roller shutter
Type of door lock	Keyed locks
Access aperture	2760mm W x 2860mm H
Paint specification	A high build, quick drying primer/topcoat paint specifically designed for use directly on to metal or bare steel, this paint contains zinc phosphate anti-corrosive pigments and is applied with a minimum dry film thickness of 75 microns.

Chargeable Options:

- Air vents
- Galvanised steel grid mesh



Please notify us at the time of ordering if you require any of these options.