

## 1 Hour Fire Rated Store - CS2FR

Backed by our 20 year structural guarantee - details available on request.

A rolled hollow welded frame creates a strong structure for this fire rated drum store. The walls, 1250mm wide hinged-doors and roof have been in-filled with Rockwool Firebatt insulation and covered with sheet steel to provide 1 hour fire rating.

A fully seam welded sump, with profiled rib strengtheners, creates a bunded area in case of a spill and base plinths eliminate contact with the ground. High and low level vents fitted with intumescent elements allow air to circulate.

However in the event of a fire, these elements will expand and seal the vents, this takes place at temperatures above 150°C.

Shelving is provided on both sides of the store, the bulkhead door, fitted with a single cam door gear mechanism, can be secured with a padlock (not supplied).

The sump fully complies with all the UK regulations relating to sump capacities.



SPECIFICATION	
External size	3000mm L x 2440mm W x 2658mm H at the highest point on the unit
No of containers	72 x 25ltr
Number of rack sets	2
Rack set size	1930mm L x 620mm W x 1800mm H (overall)
Walk-in area internal size	1760mm x 2900mm
Load capacity per shelf	500kg
Sump capacity	1080ltr
Colour	Green RAL 6029
Tare weight	1800kg
Type of doors	1 hinged
Access aperture	1250mm W x 2170mm H
Paint specification	A high build, quick drying primer/topcoat paint specifically designed for use directly on to metal or bare steel, this paint contains zinc phosphate anti-corrosive pigments and is applied with a minimum dry film thickness of 75 microns.

