

Decontamination Shower - 14 Nozzle, Self-Drain - EDS

Manufactured using galvanised pipe work which is protected with an anti-corrosive Polyamide 11 high visibility yellow plastic coating to give good resistance to acids, bases, seawater and oils. The decontamination shower is fitted with 14 spray heads to provide full body coverage and activation occurs as soon as the treadle plate is stepped on.

This decontamination shower is fitted with an automatic drain system to remove residual water after use and has been designed to meet and exceed the internationally recognised standards: EN15154 parts 1 & 2, DIN12899.3 and ANSI Z358.1.

FEATURES

| | |
|----------------------|--|
| Water inlet | 1 1/4" BSP |
| Water inlet pressure | Recommended 2 bar with a maximum of 8 bar - please notify us prior to ordering if your water pressure is below 1.5 bar |
| Water flow rate | Regulated at 110lpm |
| Operation | Foot treadle |
| Water valve | Automatic drain |
| Total weight | 50kg |
| Dimensions | 104 x 87 x 13cm |



EMPTEEZY LTD.

Muir Road Houston Industrial Estate Livingston EH54 5DR

Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466

e-mail: sales@empteezy.co.uk | www.empteezy.co.uk

Registered in Scotland 100049