

Self Drain Combination Shower - FSCS-SD

Manufactured using galvanised pipe work which is protected with an anti-corrosive Polyamide 11 high visibility yellow plastic coating to give good resistance to acids, bases, seawater and oils, all fittings are brass and the 250mmØ shower head and eyewash bowl are manufactured from ABS reinforced plastic. The eyewash has two high flow, aerated low pressure outlets fitted with automatic opening dust covers.

This combination safety shower and eyewash is fitted with an automatic drain system to remove residual water after use and has been designed to meet and exceed the internationally recognised standards: EN15154 parts 1 & 2, DIN12899.3 and ANSI Z358.1.

FEATURES

Water inlet	1 1/4" BSP
Water inlet pressure	Recommended 2 bar with a maximum of 8 bar - please notify us prior to ordering if your water pressure is below 1.5 bar
Shower flow rate	Regulated at 110lpm
Shower operation	Pull handle
Shower valve	Automatic drain & full bore 1 1/4"
Eyewash flow rate	22lpm
Eyewash operation	Push paddle & foot treadle
Eyewash valve	Automatic drain & full bore 1/2"
Waste	1 1/4" BSP
Total weight	21kg
Dimensions	76 x 25 x 20cm



EMPTEEZY LTD.

Muir Road Houstoun Industrial Estate Livingston EH54 5DR

Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466

e-mail: sales@empteezy.co.uk | www.empteezy.co.uk

Registered in Scotland 100049