

## Combination Shower - Part Stainless Steel - FSCS-SSHB

Manufactured using galvanised pipe work which is protected with an anti-corrosive Polyamide 11 high visibility yellow plastic coating to give good resistance to acids, bases, seawater and oils, all fittings are brass and the 250mmØ shower head and eyewash bowl are manufactured from stainless steel. The eyewash has two high flow, aerated low pressure outlets fitted with automatic opening dust covers.

This combination safety shower and eyewash has been designed to meet and exceed the internationally recognised standards: EN15154 parts 1 & 2, DIN12899.3 and ANSI Z358.1.

### FEATURES

Water inlet	1¼" BSP
Water inlet pressure	Recommended 2 bar with a maximum of 8 bar - please notify us prior to ordering if your water pressure is below 1.5 bar
Shower flow rate	Regulated at 110lpm
Shower operation	Pull handle
Shower valve	Full bore 1"
Eyewash flow rate	22lpm
Eyewash operation	Push paddle
Eyewash valve	Full bore ½"
Waste	1¼" BSP
Total weight	18kg
Dimensions	76 x 26 x 22cm



### EMPTEEZY LTD.

Muir Road Houstoun Industrial Estate Livingston EH54 5DR

**Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466**

e-mail: [sales@empteezy.co.uk](mailto:sales@empteezy.co.uk) | [www.empteezy.co.uk](http://www.empteezy.co.uk)

Registered in Scotland 100049