

## Floor Mounted Safety Shower with Stainless Steel Shower Head & Bowl - FSCS-SS

Manufactured using stainless steel pipe work and fittings; including the 250mmØ shower head and eyewash bowl making it ideal for harsh environments and industries such as food and pharmaceutical. The eyewash has two high flow, aerated low pressure outlets fitted with automatic opening dust covers.

This combination safety shower and eyewash has been designed to meet and exceed the internationally recognised standards: EN15154 parts 1 & 2, DIN12899.3 & ANSI Z358.1.

You may require an appropriate size/capacity fork lift truck to offload this item from the delivery vehicle. Our standard delivery doesn't include any offloading.

### FEATURES

Water inlet	1 1/4" BSP
Water inlet pressure	Recommended 2 bar with a maximum of 8 bar - please notify us prior to ordering if your water pressure is below 1.5 bar
Shower flow rate	Regulated at 110lpm
Shower operation	Pull handle
Shower valve	Full bore 1"
Eyewash flow rate	22lpm
Eyewash operation	Push paddle
Eyewash valve	Full bore 1/2"
Waste	1 1/4" BSP
Total weight	20kg
Dimensions	76 x 26 x 22cm



### EMPTEEZY LTD.

Muir Road Houstoun Industrial Estate Livingston EH54 5DR

Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466

e-mail: sales@empteezy.co.uk | www.empteezy.co.uk

Registered in Scotland 100049