

Combination Shower - ABS Plastic Shower Head & Basin - FSCS

Manufactured using galvanised pipe work which is protected with an anti-corrosive Polyamide 11 high visibility yellow plastic coating to give good resistance to acids, bases, seawater and oils, all fittings are brass and the 250mmØ shower head and eyewash bowl are manufactured from ABS reinforced plastic. The eyewash has two high flow, aerated low pressure outlets fitted with automatic opening dust covers.

This combination safety shower and eyewash has been designed to meet and exceed the internationally recognised standards: EN15154 parts 1 & 2, DIN12899.3 and ANSI Z358.1.



| FEATURES | |
|----------------------|--|
| Water inlet | 1 1/4" BSP |
| Water inlet pressure | Recommended 2 bar with a maximum of 8 bar - please notify us prior to ordering if your water pressure is below 1.5 bar |
| Shower flow rate | Regulated at 110lpm |
| Shower operation | Pull handle |
| Shower valve | Full bore 1" |
| Eyewash flow rate | 22lpm |
| Eyewash operation | Push paddle |
| Eyewash valve | Full bore 1/2" |
| Waste | 1 1/4" BSP |
| Total weight | 18kg |
| Dimensions | 76 x 26 x 22cm |

EMPTEEZY LTD.

Muir Road Houstoun Industrial Estate Livingston EH54 5DR

Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466

e-mail: sales@empteezy.co.uk | www.empteezy.co.uk

Registered in Scotland 100049