

HIBC/B - Intermediate Bulk Container Heater

Versatile and robust in construction the HIBC/B is for use with standard 1000ltr IBC and delivers critical process heating that can be specifically controlled depending on the volume of the IBC contents. The silicone insulated heating element is stitched into a jacket made from a water resistant, flame retardant Polyester material and insulated with a thermally efficient E-glass fibre insulation blanket to ensure that the power is directed effectively in to the application. The jacket is fitted with quick release buckles for ease of installation/removal and to further assist fitting it has 5 polypropylene mounting hooks along the top edge of the jacket enabling quick and efficient handling during fitting. The final construction of the heater



SPECIFICATION	
Material	Flame retardant Polyester
Insulation	E-glass fibre blanket
Element	Silicone insulated spiral wound resistance element
Thermostat	0°C to +40°C or 0°C to +90°C
Power Cable	4 Metre HO7RN-F
Voltage	110 or 230 Volts
Power Rating Options	1000W x 2
Fixing	Polyester webbing with quick release adjustable buckles & 5 x polypropylene mounting hooks

Please specify thermostat type and power rating required



EMPTEEZY LTD.

Muir Road Houston Industrial Estate Livingston EH54 5DR

Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466

e-mail: sales@empteezy.co.uk | www.empteezy.co.uk

Registered in Scotland 100049