

Steel Secure Economy Store - MDL3M

The side and roof panels are manufactured from cold rolled corrugated galvanised steel and for additional strength the unit has a structural frame which is fitted at each end and the centre of the unit. The double doors, fitted with 3 upper and 3 lower vents in each door, are located in one of the "short" sides of the unit and are secured with a Kale mortis lock with cylinder (152 R). Inside the unit is fitted with two sets of shelves (60 kg/shelf distributed load) on each of the "long" side.

The sump is manufactured from structural grade galvanised steel and is fitted with base plinths to keep the underside out of contact with the ground.

Notes: This unit will be delivered by an articulated vehicle, therefore please ensure that a vehicle of this size can access your premises before ordering and advise us accordingly.

You will require an appropriate size/capacity fork lift truck to offload this item from the delivery vehicle. Our standard delivery doesn't include any offloading.

The unit must be positioned on a solid level surface, ideally concrete of circa 150mm in depth and 100mm bigger overall than the unit. The purpose of this is to ensure the unit does not settle unevenly when loaded.



SPECIFICATION	
External size	2184mm L x 2928mm W x 2198mm H
Internal	2018mm L x 2840mm W x 1935mm H
Sump capacity	560ltr
Colour	Galvanised silver
Tare weight	650kg

