

SB450 - (CB450 + Geotextile)

Silt Booms are designed to prevent silt contamination of waterways caused by manmade or natural erosion, these fast to assemble and deploy booms are ideal for sheltered and inland waters. Because the geotextile skirts are prone to wear and tear you can purchase new skirts as a separate item if required.

Note - Freeboard = Vertical height of the product above the water. Draft = Depth of the product below the water.



SPECIFICATION	
Freeboard	150mm
Draft	300mm PVC + geotextile 2500mm, 5000mm or custom size
Overall	2950mm / 5450mm
Section lengths	25m or custom lengths
Weight	2.2 kg per metre + geotextile
Packaging Volume	0.55m ³ per 25m + geotextile
Ballast	8mm galvanised chain + 4mm chain for geotextile
Fabric	Orange or yellow 850gsm woven polyester scrim coated with PVC
Breaking strength	ASTM D 5035 (lengthwise & width wise 300kgf/5cm)
Operational Temperature	0°C to +60°C
Connections	Boom Extruded aluminium ASTM 962 (standard 1500kgf/5cm) - Geotextile Velcro



EMPTEEZY LTD.

Muir Road Houston Industrial Estate Livingston EH54 5DR

Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466

e-mail: sales@empteezy.co.uk | www.empteezy.co.uk

Registered in Scotland 100049