

Drum & IBC Store - DPU16-4HS

Backed by our 20 year structural guarantee*

The base of this unit is manufactured from mild steel sheet and uses RHS cross members and pressed ribs for additional strength. All the corner posts and shelves, main rails and cross members are manufactured from rolled hollow section and the back, sides and door panels are pressed from mild steel sheet which is corrugated where required.

The sloping roof is pressed and fitted with suitable bracing, welded around the perimeter and fitted with crane lifting points, and the double steel sliding doors run on easy glide track. Constructed from mild steel and with storage all on one level, the sump is fully seam welded and fitted with galvanised steel pallet channels (3 per pallet space). The sump as you would expect complies fully with all current UK regulations relating to sump capacities and the underside is fitted with plinths to eliminate contact with ground and reduce the risk of corrosion. Prior to painting the unit is fully shot blasted to provide a clean and keyed surface.

This model can hold up to 16 x 205ltr or 4 x 1000ltr IBC and will accommodate standard 1200mm x 1200mm, 1200mm x 1000mm and 1200mm x 800mm pallets.

*Full details available on request



SPECIFICATION	
External size	5920mm L x 1500mm W x 1806mm H at the highest point of the unit
Nº of containers	16 x 205ltr - vertical
Sump capacity	2200ltr
Colour	Green RAL 6029
Tare weight	1200kg
Type of doors	2 sliding
Type of door lock	Padlock point (Padlock not supplied) & keyed lock
Access apertures	2760mm W x 1320mm H
Paint specification	A high build, quick drying primer/topcoat paint specifically designed for use directly on to metal or bare steel, this paint contains zinc phosphate anti-corrosive pigments and is applied with a minimum dry film thickness of 75 microns.

Chargeable Options:

- Air vents
- Galvanised steel grid mesh



Please notify us at the time of ordering if you require any of these options.