

## Single Outlet Bench Mounted Drench Hose - TMSH

The drench hose head is manufactured from galvanised steel with brass fittings and is protected with an anti-corrosive Polyamide 11 high visibility yellow plastic coating which provides good resistance to acids, bases, seawater and oils, while the 1.5m flexible hose is stainless steel.

The drench hose outlet provides hi-flow aerated water at low pressure and is fitted with an automatic opening anti-dust cover.

This single outlet bench mounted drench hose has been designed to meet and exceed the internationally recognised standards: EN15154 parts 1 & 2, DIN12899.3 and ANSI Z358.1



### FEATURES

Water inlet	1/2" BSP
Water inlet pressure	Recommended 2 bar with a maximum of 8 bar - please notify us prior to ordering if your water pressure is below 1.5 bar
Flow rate	15lpm
Operation	Trigger
Total weight	2kg
Dimensions	36 x 27 x 8cm



### EMPTEEZY LTD.

Muir Road Houston Industrial Estate Livingston EH54 5DR

**Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466**

e-mail: [sales@empteezy.co.uk](mailto:sales@empteezy.co.uk) | [www.empteezy.co.uk](http://www.empteezy.co.uk)

Registered in Scotland 100049