

## Wall Mounted Emergency Eyewash ABS Plastic - WMEW

The eyewash assembly and eyewash bowl are manufactured from ABS reinforced plastic and the bowl is fitted with two high flow, aerated low pressure outlets fitted with automatic opening dust covers. All fittings are brass and are protected with an anti-corrosive Polyamide 11 high visibility yellow plastic coating which provides good resistance to acids, bases, seawater and oils.

This wall mounted eyewash has been designed to meet and exceed the internationally recognised standards: EN15154 parts 1 & 2, DIN12899.3 and ANSI Z358.1.



FEATURES	
Water inlet	1/2" BSP
Water inlet pressure	Recommended 2 bar with a maximum of 8 bar - please notify us prior to ordering if your water pressure is below 1.5 bar
Eyewash flow rate	22lpm
Eyewash operation	Push paddle
Eyewash valve	Full bore 1/2"
Waste	1 1/4" BSP
Total weight	3kg
Dimensions	51 x 36 x 13cm



### EMPTEEZY LTD.

Muir Road Houstoun Industrial Estate Livingston EH54 5DR

**Tel: +44 (0)1506 430309 Fax: +44 (0)1506 441466**

e-mail: [sales@empteezy.co.uk](mailto:sales@empteezy.co.uk) | [www.empteezy.co.uk](http://www.empteezy.co.uk)

Registered in Scotland 100049