

## VTE350 - Tank-Fed Eye Wash

Suitable for all climates and manufactured to ANSI Z358.1-2014 and EN15154 standards, this tank-fed eye wash guarantees over 30 minutes of tepid water without the need of a mains water supply. The unit is completely corrosion resistant and suitable for hazardous or non-hazardous environments. Comes with water level indicator and temperature display as standard.

### Key Features

- Guaranteed tepid water
- Highly visible
- Manufactured in house, in the UK
- One-piece insulated GRP header tank



\*Shown with optional panelling

OPERATING CONDITIONS	
Water Supply Pressure	0.5 - 6 bar
Temperature	-25°C to +60°C (water chiller recommended for temperatures above 35°C)
TECHNICAL DETAILS	
Inlet Connection	1" BSPM (flanged options available)
Screened Overflow	40mm PVC-U
Eye Wash Flow Rate	Min 1.5lpm (per nozzle)
Ball Float Valves for quick refill	2 x 3/4" stainless valves with 6" plastic floats
Eye Wash Operation	Lift lid (stainless foot operation as option)
Signage	Self-adhesive photoluminous pictorial sign
MATERIAL DETAILS	
Header Tank	350L green insulated GRP (other colours available)
Header Tank Lid	White insulated GRP
Shower Frame	304 stainless steel as standard (316 as option)
Eye Wash	Yellow GRP + 2 low pressure nozzles
Operating Valve	Stainless steel
Panelling - if fitted	Side & rear - green GRP
Overhead Sun Canopy - if fitted	White insulated GRP
Eye Wash Foot Treadle - if fitted	Stainless steel (powder coated red for high visibility)
Temperature Gauge - if fitted	Stainless steel - 150mm diameter
Water Heater - if fitted	2.4Kw (Non-hazardous)

## VTE350 - Tank-Fed Eye Wash

### Optional Extras

- Flexible face/body wash
- Eye wash foot treadle
- Side & rear panelling
- Drain sump
- Sun canopy
- Heavy duty strip curtain
- Manual drain valve
- Water heater
- Water chiller
- Low energy lighting
- Temperature gauge
- Flashing alarm & siren
- Remote alarm
- Legionelle kit

### Technical Drawings

