



Safety Data Sheet

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia
Date of Revision: 12/11/2020 Revision: 04

Section 1 - Chemical Product and Company Identification

1.1 Product Name: Cetanium

1.2 Synonym: Blend

1.3 Manufacturer: VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

1.4 Supplier: VP Racing Fuels Pty Ltd, Unit 24 85-115 Alfred Road, Chipping Norton, NSW 2170, Australia 02 9723 4233, **Emergency Telephone:** 0421 116 838.

1.5 Recommended Use: **THIS ADDITIVE IS FOR DIESEL FUEL USE ONLY!**

1.6 Emergency Response Number: CHEMTREC 800-424-9300

International Emergency Telephone Number: +1-703-527-3887

CHEMTREC Australia (Sydney) +(61) 290372994

1.7 Poison Control Centre: 13 11 26, 24 hours a day from anywhere in Australia.

Section 2 - Hazards Identification

GHS HAZARD

2.1 Hazard Classes

Flammable liquid/vapor

Specific Target Organs toxicity single exposure

Specific Target Organs repeated exposure

Skin Irritation

Acute Toxicity (Oral)

Acute Toxicity (Inhalation)

Acute Toxicity (Dermal)

Aspiration Hazard

Carcinogenicity

Toxic to Aquatic Life Long-lasting effects

Hazard Categories

Category 3

Category 3

Category 2

Category 2

Category 4

Category 4

Category 4

Category 1

Category 2

Category 2

2.2 Signal Word: **Danger**

Cetanium

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia



2.3 Pictograms:

Flame Health hazard Irritant Toxic to aquatic life

2.4 Hazard Statements

PHYSICAL HAZARDS:

H226: Flammable liquid and vapor.

HEALTH HAZARDS:

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enter the airway.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H351: Suspected of causing cancer.

H373: May causes damage to organs through prolonged or repeated exposure.

ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long-lasting effects.

PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children.

P201: Obtain special instructions before use.

READ SDS BEFORE USE.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from sparks and open flames-
No smoking.

H223: Keep the container tightly closed.

P240: Ground or bond container and receiving equipment.

P241: Use explosion-proof equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260: Do not breathe vapors.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink, or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves, clothing, and eye protection.

Cetanium

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

RESPONSE STATEMENTS:

P301 +P310+ P331: IF SWALLOWED:
Immediately call a poison center or doctor. DO NOT induce vomiting.
P303+P361+P353: IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340: IF INHALED: Remove to fresh air and keep comfortable for breathing
P308+P313: If exposed or concerned, get medical attention.
P313+P332: If skin irritation persists, get medical attention.
H314: Get medical attention if you feel unwell.
P330: Rinse mouth.
P362+P364: IF ON CLOTHING, take off contaminated clothing and wash it before reuse.
P370+P378: In case of fire, use foam, carbon dioxide, dry chemical to extinguish a fire.
P391: Collect spillage.

STORAGE STATEMENTS:

P403+P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.

DISPOSAL STATEMENTS:

P501: Dispose of content and container following local, regional, national or international regulations

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: AUH066 Repeated exposure may cause skin dryness and cracking.

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	Classification
N/A	N/A	Blend of Hydrocarbon and normally organic compounds	100	None

Cetanium

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

3.2 Blend Contains

Chemical Names	CAS#	EC#	Classification
Diesel Fuel	68476-34-6	270-676-1	Flam. Liq. 3 H226, Asp. Tox. 1 H304 Skin Irrit. 2 H315, Acute Tox. 4 H332, STOT RE 2 H373, Carc.2 H351, Aquatic Chronic 2 H411
Nitronal	27247-96-7	248-363-6	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Aquatic Chronic 2 H411
TOU	4431-83-8	224-631-8	Not Classified

3.3 Trade Secret Provision and Chemical Concentration Disclosure: Following GHS Regulations, we have withheld specific percentages of the mixture's chemicals. The chemical concentrations have been disclosed as a blend and applicable to the hazards identified in this Safety Data Sheet.

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can irritate. Symptoms may include discomfort or pain and redness.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Prolonged and repeated liquid contact can cause defatting and drying of the skin and lead to irritation and dermatitis.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

4.3 Ingestion: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema, and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.4 Inhalation: Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

4.5 Note to Physicians: *After first aid, get appropriate paramedic or community medical support.*

The severity of the outcome following exposure may be related to the time between the exposure and treatment, rather than the amount of exposure. Therefore, there is a need for rapid treatment of any exposure.

4.6 If you determine that a medical emergency exists and the specific chemical percentages are necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical percentages. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement, following OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

Cetanium

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

Section 5 - Fire-Fighting Measures

5.1 General Fire Hazards: Use water to cool containers exposed to fire.

5.2 Hazardous Combustion Products: Avoid fumes of burning products.

5.3 Extinguishing Media: Carbon dioxide, dry chemical, foam.

5.4 Fire Fighting Equipment/Instructions Firefighters should wear full-face, self-contained breathing apparatus, and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

6.1 Spill /Leak Procedures: Ventilate area highly flammable. Spillages of the liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

6.2 Spills: Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place it in a container for disposal.

Section 7 - Handling and Storage

7.1 Handling Precautions: Keep away from ignition sources such as heat, sparks, and open flames. NO SMOKING Take precautionary measures against static discharge. Non-sparking tools should be used. Wear protective gloves, clothing, and eye protection. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment. Empty containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other ignition sources. They may explode and cause injury or death.

7.2 Storage Requirements: Store in original manufacture container tightly closed container in a cool, dry, and well-ventilated area.

7.3 Chemical Incompatibilities: Strong oxidizing agents and strong reducing agents.

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OEL
Blend of Hydrocarbon and normally organic compounds	100 mg/m ³ TWA (Inhalable fraction and vapor.)	None Shown

8.2 ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.

8.3 OEL = OCCUPATIONAL EXPOSURE LIMITS

8.4 TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded."

8.5 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Cetanium

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

8.6 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder before reuse.

Remove this material from your shoes and clean personal protective equipment.

8.7 Personal protective equipment

Respiratory protection

Where risk assessment shows, air-purifying respirators are appropriate, use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Impervious clothing flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

8.9 Protective Clothing Pictograms



Splash Goggles



Gloves



Protective Apron



Vapor Respirator

Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Various

Odor: Hydrocarbon Odor

Vapor Pressure: Not Available

Vapor Density (Air=1): >1

Specific Gravity (H₂O=1,): Not Available

Relative Density: Not Available

Odor Threshold: Not Available

Flammability (solid, gas): Not applicable.

Evaporation rate: Not Available

Partition coefficient octanol/water: Not Available

Water Solubility: Insoluble

Flash Point: 52°C closed cup

Boiling Point/Range 320°F (160°C)

Lower Explosive Limits (vol % in air): .6%

Upper Explosive Limits (vol % in air): 7.5%

Melting Point Not Data Available

Viscosity: <20.5mm²/s @104°F 40°C

Autoignition Temperature: Not Data Available

Decomposition temperature: Not Available

pH: None

Cetanium

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide

10.5 Conditions to Avoid: Avoid heat, sparks, open flames, and other ignition sources

Section 11- Toxicological Information

11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 1099 mg/kg

ATE (Dermal): 1900 mg/kg

ATE (Inhalation vapor/mist): 4 mg/l mist

11.1.1 OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Oral Toxicity.

11.1.2 OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Dermal Toxicity.

11.1.3 OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Inhalation Toxicity.

11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin, and Eye Contact.

11.3 Aspiration Hazard: European Chemical Agency Data Base shows that this product's components may be fatal if swallowed and enters airways.

11.4 Mutagenicity: OECD Guideline Test results found in the European Chemical Agency Database show no components cause genetic defects.

11.5 Skin Corrosion/Irritation: OECD Guideline Test results found in the European Chemical Agency Database show that components cause skin irritation. Repeated exposure may cause skin dryness or cracking.

11.6 Serious Eye Damage/Irritation: OECD Guideline Test results found in the European Chemical Agency Database show that no product components cause serious eye irritation. However, it can cause redness, discomfort, and irritate your eyes.

11.7 Reproductive toxicity: OECD Guideline Test results found in the European Chemical Agency Database show no components to cause damage to fertility or the unborn child.

11.8 Skin Sensitization OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause skin sensitivity.

11.9 Respiratory Sensitization OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause respiratory sensitivity.

Cetanium

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

11.10 Specific Target Organ Toxicity (Single Exposure): European Chemical Agency Database shows that no components may cause damage organs due to a single exposure.

11.11 Specific Target Organ Toxicity (Repeated Exposure): Contains chemicals that may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

11.12 Signs and Symptoms: Effects due to exposure may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Symptoms may be delayed.

11.13 Carcinogenicity: OECD Guideline Test results found in the European Chemical Agency Database show that this product's components can cause cancer.

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Blend of Hydrocarbon and normally organic compounds	Expected to be toxic to aquatic organisms, which will cause long-term adverse effects in the environment		

Toxicity: OECD Guideline Test results found in the European Chemical Agency Database show this product's components to cause long-term toxicity to aquatic life.

12.2 Mobility: Floats on water

12.3 Persistence/degradability: Inconclusive technical data.

12.4 Bioaccumulation: Inconclusive technical data.

12.5 Other adverse effects: Inconclusive technical data.

12.6 Other Adverse Effects: Not available on this mixture

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! The container should be completely emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Cetanium

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

Section 14 - Transport Information

14.1 Australien Transport Information



ID No.: UN 3295

Shipping Name: Hydrocarbons, liquid, n.o.s.

Hazard Class: 3

Packing Group: III

Marking: MARINE POLLUTANT Nitronal

Label: Flammable

Placard: Flammable

HAZCHEM Code: 3YE(3), HIN 33

14.2 IMDG Transport Information



ID No.: UN 3295

Shipping Name: HYDROCARBONS, LIQUID, N.O.S.

Hazard Class: 3

Packing Group: III

Flash Point: 52 °C - closed cup


EmS Number: F-E, S-D

Marking: Marine Pollutant Nitronal

Label: Flammable

Placard: Flammable

14.3 UN Dangerous Goods Transport Information



ID No.: UN 3295

Shipping Name: Hydrocarbons, liquid, n.o.s.


Hazard Class: 3

Packing Group: III

Marking: MARINE POLLUTANT Nitronal


Label: Flammable

Placard: Flammable



Cetanium

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia




14.4 DOT Transport Limited Quantity/Consumer Commodity

Inner packaging not over

5.0L (1.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each



14.5 IMDG Transport Limited Quantity

Inner packaging not over 5.0L (1.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

ID No.: UN 3295

Shipping Name: HYDROCARBONS, LIQUID, N.O.S.LTD. QTY.

Hazard Class: 3

Packing Group: III

Flash Point: (52° C c.c.)

EmS Number: F-E, S-D

Section 15 - Regulatory Information

15.1

Australian manufacturers' and importers' obligations under the WHS Regulations: All components of this product are on the Inventory or are exempt from Inventory requirements.

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall determine the product's suitability for their particular purpose and on the condition that they assume the risk of their use.

16.2 References: CHEMpendium Database of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller online, European Chemical Agency Database, and MSDS and SDS of chemicals in this mixture.

Cetanium

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

16.3 SDS Preparation Date: 01/28/2016

SDS Previous Issue Date: None

SDS Revision Date: 07/17/2017 Revised sections 2,4,9,11,12

SDS Revision Date: 09/21/2017 Revised sections 3.15.16

SDS Revision Date: 12/15/2017 Revised section 2,11

SDS Revision Date: 12/11/2020 Revised sections 1,2,3,8,9,11,12,14,15,16

Prepared by SJC Compliance Education, Inc.

1319 Varese Drive

Pearland TX 77581

steve@sjcedu.org

END OF SAFETY DATA SHEET

