

# Safety Data Sheet

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia Date of Revision: 12/13/2020 Revision: 04

# **Section 1 - Chemical Product and Company Identification**

- 1.1 Product Name: Power Boost
- 1.2 Synonym: Blend
- 1.3 Manufacturer: VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112,

210.635.7744

1.4 Supplier: VP Racing Fuels Pty Ltd, Unit 24 85-115 Alfred Road, Chipping Norton, NSW

2170, Australia 02 9723 4233, Emergency Telephone: 0421 116 838.

- **1.5** Recommended Use: Fuel System Treatment.
- 1.6 RESTRICTIONS on USE THIS FUEL INJECTION CLEANER IS FOR GASOLINE

## **ENGINES ONLY.**

1.7 Emergency Response Number: CHEMTREC 800-424-9300 International Emergency Telephone Number: +1-703-527-3887

CHEMTREC Australia (Sydney) +(61) 290372994

**1.8 Poison Control Centre:** 13 11 26, 24 hours a day from anywhere in Australia.

## **Section 2 - Hazards Identification**

# **GHS HAZARD**

2.1 <u>Hazard Classes</u>	<b>Hazard Categories</b>
Flammable liquid/vapor	Category 3
<b>Specific Target Organs toxicity single exposure</b>	Category 3
Specific Target Organs repeated exposure	Category 2
Eye Irritation	Category 2A
Skin Irritation	Category 2
Acute Toxicity (Oral)	Category 4
Acute Toxicity (Inhalation)	Category 4
Aspiration Hazard	Category 1
Toxic to Aquatic Life Long Lasting Effects	Category 2

# 2.2 Signal Word: Danger

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia



# 2.3 Pictograms:

Flame Health hazard

Irritant Toxic to aquatic life

# 2.4 Hazard Statements

PHYSICAL HAZARDS: H226: Flammable liquid and vapor.

HEALTH HAZARDS: H302: Harmful if swallowed.

H304: May be fatal if swallowed and enter the

airway.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H361: Suspected of damaging fertility or the

unborn child.

H336: May cause drowsiness or dizziness. H373: Causes damage to organs through

prolonged or repeated exposure.

ENVIRONMENTAL HAZARDS: H411: Toxic to aquatic life with long-lasting

effects.

PRECAUTIONARY STATEMENTS: P102: Keep out of reach of children.

P201: Obtain special instructions before use.

**READ SDS BEFORE USE.** 

P202: Do not handle until all safety precautions

have been read and understood.

P210: Keep away from sparks and open flames-

No smoking.

H233: Keep the container tightly closed.

P240: Ground or bond container and receiving

equipment.

P241: Use explosion-proof equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against

static discharge.

P260: Do not breathe vapors.

P264: Wash hands thoroughly after handling

P270: Do not eat, drink, or smoke when using

this product.

P271: Use only outdoors or in a well-ventilated

rea.

P273: Avoid release to the environment.

P280: Wear protective gloves, clothing, and eye

protection.

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

RESPONSE STATEMENTS: P301 +P310+ P331: IF SWALLOWED: Immediately

call a poison center or doctor. DO NOT induce

vomiting.

P302+P352: IF ON SKIN: Wash with plenty of

water.

P304+P340: IF INHALED: Remove to fresh air

and keep comfortable for breathing.

P305+P351: IF IN EYES: Rinse cautiously with

water for at least 15 minutes.

P308+P313: If exposed or concerned, get

medical attention.

P313+P332+P337: If skin or eye irritation

persists, get medical attention.

H314: Get medical attention if you feel unwell.

P330: Rinse mouth.

P362+P364: IF ON CLOTHING, take off contaminated clothing and wash it before

reuse.

P370: In case of fire, use foam, carbon dioxide,

dry chemical to extinguish a fire

STORAGE STATEMENTS: P403+P235: Store in a well-ventilated place.

Keep cool.

P405: Store locked up.

DISPOSAL STATEMENTS: P501: Dispose of content and container

following local, regional, national, or

international regulations

**2.5** Hazards not otherwise classified (HNOC) or not covered by GHS: AUH066 Repeated exposure may cause skin dryness and cracking.

# **Section 3 - Composition / Information on Ingredients**

#### 3.1

CAS#	EC#	Chemical Name	Percent	Classification
N/A	N/A	Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	68-75%	None
111-76-2	203-905-0	3-Oxa-1-heptanol	20-30%	Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Irrit. 2 H315, Eye Irrit 2 H319, Acute Tox. 4 H332
73398-61-5	277-452-2	Glycerides, mixed decanoyl, and octanoyl	2-5%	Eye Irrit 2 H319

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

#### 3.2 Blend Contains

Chemical Names	CAS#	EC#	Classification
Distillates, Hydrotreated light	64742-47-8	265-149-8	Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411
Phenylmethane	108-88-3	203-625-9	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319 STOT SE 3 Central nervous Sys Inhalation H336, Repr. 2 H361, STOT RE 2 Central nervous sys H373

**3.3** Trade Secret Provision and Chemical Concentration Disclosure: Following GHS Regulations, we have withheld specific percentages of the mixture's chemicals. The chemical concentrations have been disclosed as a blend and applicable to the hazards identified in this Safety Data Sheet.

## **Section 4 - First Aid Measures**

**4.1 Eye:** Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage

**Eyes:** Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

**4.2 Skin:** Prolonged and repeated liquid contact can cause defatting and drying of the skin and lead to irritation and dermatitis.

**Skin:** Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

**4.3 Ingestion:** Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema, and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

**4.4 Inhalation:** Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

**Inhalation:** Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

- **4.5** Note to Physicians: After first aid, get appropriate paramedic or community medical support. The severity of the outcome following exposure may be related to the time between the exposure and treatment, rather than the amount of exposure. Therefore, there is a need for rapid treatment of any exposure.
- 4.6 If you determine that a medical emergency exists and the specific chemical percentages are necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical percentages. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement, following OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

# **Section 5 - Fire-Fighting Measures**

- **5.1 General Fire Hazards:** Use water to cool containers exposed to fire.
- **5.2 Hazardous Combustion Products:** Avoid fumes of burning products.
- **5.3 Extinguishing Media:** Carbon dioxide, dry chemical, foam.
- **5.4** Fire Fighting Equipment/Instructions Firefighters should wear full-face, self-contained breathing apparatus, and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

## **Section 6 - Accidental Release Measures**

- **6.1 Spill /Leak Procedures:** Ventilate area flammable. Spillages of the liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.
- **6.2 Spills:** Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place it in a container for disposal.

# **Section 7 - Handling and Storage**

- **7.1** Handling Precautions: Keep away from ignition sources such as heat, sparks, and open flames. NO SMOKING Take precautionary measures against static discharge. Non-sparking tools should be used. Wear protective gloves, clothing, and eye protection. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment. Empty containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other ignition sources. They may explode and cause injury or death.
- **7.2 Storage Requirements:** Store in original manufacture container tightly closed container in a cool, dry, and well-ventilated area.
- **7.3 Chemical Incompatibilities:** Strong oxidizing agents and strong reducing agents.

# **Section 8 - Exposure Controls / Personal Protection**

#### 8.1

0.1			
Chemical Names	ACGIH- TLV	OEL	
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	20 ppm TWA	50 ppm TWA	
3-Oxa-1-heptanol	25 ppm TWA	20 ppm TWA	
Glycerides, mixed decanoyl, and octanoyl	Not Established	Not Established	

- 8.2 ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.
- 8.3 OEL = OCCUPATIONAL EXPOSURE LIMITS
- **8.4 TWA Means** "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded."

#### Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

- **8.5 Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.
- **8.6 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder before reuse.

Remove this material from your shoes and clean personal protective equipment.

#### 8.7 Personal protective equipment

#### Respiratory protection

Where risk assessment shows, air-purifying respirators are appropriate, use a full-face respirator with multipurpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

#### Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin and body protection

Impervious clothing flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

#### 8.9 Protective Clothing Pictograms









Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

## **Section 9 - Physical and Chemical Properties**

9.1

Physical State: Liquid
Appearance: Orange
Odor: Hydrocarbon Odor
Vapor Pressure: Not Available
Vapor Density (Air=1): >1
Specific Gravity (H2O=1,): 0.75
Relative Density: Not Available
Odor Threshold: Not Available

Flammability (solid, gas): Not Applicable.

Evaporation rate: Not Available

Partition coefficient octanol/water: Not Available

Water Solubility: Insoluble Flash Point: 42°C closed cup Boiling Point/Range 57.2 -175 °C

Lower Explosive Limits (vol % in air): 1% Upper Explosive Limits (vol % in air): 10%

Melting Point Not Data Available Viscosity: <20.5mm2/s @ 40°C

**Autoignition Temperature:** Not Data Available **Decomposition temperature:** Not Available

pH: None

# **Section 10 - Stability and Reactivity**

**10.1 Stability:** Stable under ordinary conditions of use and storage.

**10.2 Polymerization:** Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide

10.5 Conditions to Avoid: Avoid heat, sparks, open flames, and other ignition sources

# **Section 11- Toxicological Information**

11.1

The calculated Acute Toxicity Estimate Value (ATE) for this mixture:

ATE oral = 1887 mg/kg

ATE dermal = 2000 mg/kg

ATE Inhalation (vapor/mist) = 8.54mg/l mist

- **11.1.1** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Oral Toxicity.
- **11.1.2** OECD Guideline Test results found in the European Chemical Agency Database show that no product's components cause Toxic Dermal Toxicity.
- **11.1.3** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Harmful Inhalation Toxicity.
- 11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin, and Eye Contact.
- **11.3 Aspiration Hazard:** European Chemical Agency Database shows that this product's components may be fatal if swallowed and enters airways.

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

- **11.4 Mutagenicity:** OECD Guideline Tests results found in the European Chemical Agency Database show no product's components cause genetic defects.
- **11.5** Skin Corrosion/Irritation: OECD Guideline Tests results found in the European Chemical Agency Database show that this product's components cause skin irritation. Repeated exposure may cause skin dryness or cracking.
- **11.6 Serious Eye Damage/Irritation:** OECD Guideline Tests results found in the European Chemical Agency Database show that this product's components cause serious eye irritation.
- **11.7 Reproductive toxicity:** OECD Guideline Tests results found in the European Chemical Agency Database show this product's components cause damage fertility or the unborn child.
- **11.8 Skin Sensitization** OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause skin sensitivity.
- **11.9 Respiratory Sensitization** OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause respiratory sensitivity.
- **11.10** Specific Target Organ Toxicity (Single Exposure): European Chemical Agency Database shows that this product's components may cause damage the central nervous system (CNS). Human exposure above 200 ppm can cause narcosis, damage to the kidney and liver, and present an abnormal blood picture showing erythropenia, reticulocytosis, granulocytosis, leukocytosis. It would be likely to cause fragility of erythrocytes and hematuria.
- **11.11 Specific Target Organ Toxicity (Repeated Exposure):** Contains material that may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).
- **11.12 Signs and Symptoms:** Swallowing results in a sour taste that turns to a burning sensation and is followed by the tongue's numbness, which indicates paralysis of the sensory nerve endings. Central nervous system depression, headache, narcosis.
- **11.13 Carcinogenicity:** OECD Guideline Tests results found in the European Chemical Agency Database show that this product can cause cancer.

# **Section 12 - Ecological Information**

#### 12.1

Product Name	Results	Species	Exposure
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	It is expected to be toxic to aquatic organisms. May cause long-term adverse effects in the environment.		
3-Oxa-1-heptanol	LC220 mg/l	Fish	96 hours
Glycerides, mixed decanoyl, and octanoyl	LC50 >100 mg/l	Fish	96 hours

**Toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show this product's components to cause long-term toxicity to aquatic life.

**12.2 Mobility:** Floats on water.

#### Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

12.3 Persistence/degradability: Inconclusive technical data.

**12.4 Bioaccumulation:** Inconclusive technical data.

**12.5** Other adverse effects: Inconclusive technical data.

12.6 Other Adverse Effects: Not available on this mixture

## **Section 13 - Disposal Considerations**

**13.1 Disposal: DO NOT REUSE EMPTY CONTAINER!** The container should be completely emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

# **Section 14 - Transport Information**

### 14.1 Australien Transport Information



**ID No.:** UN 3295

Shipping Name: Hydrocarbons, liquid, n.o.s.

Hazard Class: 3
Packing Group: III
Label: Flammable
Placard: Flammable

Marking: Marine Pollutant Distillates, Hydrotreated light

HAZCHEM Code: 3YE(3), HIN 33

#### **14.2 IMDG Transport Information**



**ID No.:** UN 3295

**Shipping Name:** HYDROCARBONS, LIQUID, N.O.S.

Hazard Class: 3 Packing Group: III Flash Point: (42 °C c.c.) EmS Number: F-E, S-E Label: Flammable Placard: Flammable

Marking: Marine Pollutant Distillates, Hydrotreated light

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

### 14.3 UN Dangerous Goods Transport Information





**ID No.:** UN 3295

Shipping Name: Hydrocarbons, liquid, n.o.s.

Hazard Class: 3
Packing Group: III
Label: Flammable
Placard: Flammable

Marking: Marine Pollutant Naphtha (petroleum), light alkylate



## 14.4 DOT Transport Limited Quantity/Consumer Commodity

Inner packaging not over 5.0L (1.3 gallons) net capacity each. Outer Package not over 30kg (66lbs) each



## 14.5 IMDG Transport Limited Quantity

**ID No.:** UN 3295

Shipping Name: HYDROCARBONS, LIQUID, N.O.S.

Hazard Class: 3 Packing Group: III Flash Point: 42 °C c.c. EmS Number: F-E, S-E Label: Flammable Placard: Flammable

Marking: Marine Pollutant Distillates, Hydrotreated light

# **Section 15 - Regulatory Information**

15.1

**Australian manufacturers' and importers' obligations under the WHS Regulations:** All components of this product are on the Inventory or are exempt from Inventory requirements.

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

## **Section 16 - Other Information**

**16.1 Disclaimer:** The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall determine the product's suitability for their particular purpose and on the condition that they assume the risk of their use.

**16.2** References: CHEMpendium Database of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller online, European Chemical Agency Database, and MSDS and SDS of chemicals in this mixture.

**16.3 SDS Preparation Date:** 01/13/2016

SDS Previous Issue Date: None

SDS Revision Date: 01/20/2017 Revised sections 9,14

**SDS Revision Date:** 09/21/2017 Revised sections 2,3,8,11,15,16 **SDS Revision Date:** 12/21/2017 Revised sections 2,3,8,11,14 **SDS Revision Date:** 12/13/2020 Revised sections 1,2,11,14,15,16

Prepared by SJC Compliance Education, Inc. 1319 Varese Drive Pearland TX 77581 steve@sjcedu.org

**END OF SAFETY DATA SHEET** 

