



Safety Data Sheet

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia
Date of Revision: 11/02/2020 Revision: 01

Section 1 - Chemical Product and Company Identification

1.1 Product Name: **X85**

1.2 Synonyms: Blend

1.3 Manufacture: VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

1.4 Supplier: VP Racing Fuels Pty Ltd, Unit 24 85-115 Alfred Road, Chipping Norton, NSW 2170, Australia 02 9723 4233, **Emergency Telephone:** 0421 116 838.

1.5 Recommended Use: Racing Fuels

1.6 **RESTRICTIONS on USE** **THIS FUEL IS FOR RACING VEHICLE USE ONLY!**

NOT LEGAL FOR STREET DRIVEN MOTOR VEHICLE.

1.7 Emergency Response Number: **CHEMTREC 800-424-9300**

International Emergency Telephone Number: **+1-703-527-3887**

CHEMTREC Australia (Sydney) **+(61) 290372994**

1.8 Poison Control Centre: 13 11 26, 24 hours a day from anywhere in Australia.

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes

Highly Flammable liquid/vapor

Mutagenicity

Carcinogen

Aspiration Hazard

Toxic to Aquatic Life Long-Lasting Effects

Hazard Categories

Category 2

Category 1B

Category 1B

Category 1

Category 2

2.2 Signal Word: **Danger**

X85

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia



Flam

Health

Irritant

Aquatic

2.3 Pictograms:

2.4 Hazard Statements

PHYSICAL HAZARDS:

H225: Highly flammable liquid and vapor.

HEALTH HAZARDS:

H304: May be fatal if swallowed and enters airways.

H340: May cause genetic defects.

H350: May cause cancer.

ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long-lasting effects.

PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children.

P201: Obtain special instructions before use.

READ SDS BEFORE USE.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from sparks and open flames- No smoking.

P233: Keep the container tightly closed.

P240: Ground or bond container and receiving equipment.

P241: Use explosion-proof equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260: Do not breathe vapors.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink, or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves, clothing, and eye protection.

RESPONSE STATEMENTS:

P301 +P310+ P331: IF SWALLOWED:

Immediately call a poison center or doctor. DO NOT induce vomiting.

P303+P361+P353: IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water.

P308+P313: If exposed or concerned, get medical attention.

X85

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

P370+P378: In case of fire, use foam, carbon dioxide, dry chemical to extinguish a fire
P391 Collect spillage.

STORAGE STATEMENTS:

P403+P235: Store in a well-ventilated place.
Keep cool.
P405: Store locked up.

DISPOSAL STATEMENTS:

P501: Dispose of content and container following local, regional, national, or international regulations.

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: AUH066 Repeated exposure may cause skin dryness and cracking.

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	GHS Classification
64741-64-6	265-066-7	Alkylate Full Range	13-17%	Asp. Tox. 1 H304, Muta. 1B H340, Carc. 1B H350, Aquatic Chronic 2 H411
64-17-5	200-578-6	1-Hydroxyethane	83-87%	Flam. Liq.2 H225

3.2 Trade Secret Provision and Chemical Concentration Disclosure: In accordance with GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and apply to the hazards identified in this Safety Data Sheet.

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can irritate. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Prolonged and repeated liquid contact can cause defatting and drying of the skin and lead to irritation and dermatitis.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately and wash clothing before reuse.

4.3 Ingestion: Liquid ingestion can cause headaches, gastrointestinal pain, nausea, and vomiting.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.4 Inhalation: Prolonged breathing of high vapor concentrations can produce headaches, dizziness, nausea, and impaired vision.

X85

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

4.5 After first aid, get appropriate paramedic or community medical support. The severity of outcome following exposure may be related to the time between the exposure and treatment, rather than the amount of exposure. Therefore, there is a need for rapid treatment of any exposure.

4.6 Note to Physicians: If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. Call CHEMTREC at 800-424-9300 or 703-527-3887. We will require a written statement of need and confidentiality agreement, in accordance with OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

5.1 General Fire Hazards: Use water to cool containers exposed to fire.

5.2 Hazardous Combustion Products: Avoid fumes of burning products.

5.3 Extinguishing Media: Carbon dioxide, dry chemical, foam.

5.4 Fire Fighting Equipment/Instructions: Firefighters should wear full-face, self-contained breathing apparatus, and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

6.1 Spill /Leak Procedures: Ventilate area highly flammable. Spillages of the liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

6.2 Spills: Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place it in a container for disposal.

Section 7 - Handling and Storage

7.1 Handling Precautions: Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin, or clothing. Keep the container tightly closed. Avoid inhalation.

7.2 Storage Requirements: Store in a tightly closed container in a cool, dry, and well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OEL
Alkylate Full Range	Not established	Not established
1-Hydroxyethane	1000 ppm TWA	1000 ppm TWA

X85

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

8.2

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. OEL = Occupational Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

8.3 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder before reuse. Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows that air-purifying respirators are appropriate for a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

8.6 Protective Clothing Pictograms



X85

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Clear

Odor: Aromatic Hydrocarbon Odor

Vapor Pressure: Not Available

Vapor Density (Air=1): .>1

Specific Gravity (H₂O=1,): Not Available

Relative Density: Not Available

Odor Threshold: Not Available

Flammability (solid, gas): Not applicable.

Evaporation rate: Not Available

Partition coefficient octanol/water: Not Available

Water Solubility: Insoluble

Flash Point: -40 °C c.c.

Boiling Point/Range: 36.5 – 205.6°C

Freezing/Melting Point:: Not Available

LEL: 1%

UEL: 19%

Viscosity: <20.5mm²/s @ 40°C

Auto ignition Temperature: Not Available

Decomposition temperature: Not Available

pH: None

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents.

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide.

10.5 Conditions to Avoid: Avoid heat, sparks, open flames, and other ignition sources.

Section 11- Toxicological Information

11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 5000 mg/kg

ATE (Dermal): 10000 mg/kg

ATE (Inhalation vapor/mist): 23.8 mg/l

11.1.1 OECD Guideline Test results found in the European Chemical Agency Database show no product components to cause Harmful Oral Toxicity.

11.1.2 OECD Guideline Test results found in the European Chemical Agency Database show no product components to cause Harmful Dermal Toxicity.

11.1.3 OECD Guideline Test results found in the European Chemical Agency Database show no product components to cause Harmful Inhalation Toxicity.

11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin and Eye Contact

11.3 Aspiration Hazard: European Chemical Agency Data Base shows that this product's components may be fatal if swallowed and enters airways.

11.4 Mutagenicity: OECD Guideline Test results found in the European Chemical Agency Database show this product's components cause genetic defects.

X85

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

11.5 Skin Corrosion/Irritation: OECD Guideline Test results found in the European Chemical Agency Database show that no products of this blend cause skin irritation. However, it still can irritate, and repeated exposure may cause skin dryness or cracking.

11.6 Serious Eye Damage/Irritation: OECD Guideline Test results found in the European Chemical Agency Database show that no products of this blend cause eye irritation. However, it still can cause eye irritation.

11.7 Reproductive toxicity: OECD Guideline Test results found in the European Chemical Agency Database show that no products of this blend cause damage to fertility or the unborn child.

11.8 Skin Sensitization OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause skin sensitivity.

11.9 Respiratory Sensitization OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause respiratory sensitivity.

11.10 Specific Target Organ Toxicity (Single Exposure): European Chemical Agency Database shows that no products of this blend cause damage to organs due to single exposure. However, it may still damage the central nervous system (CNS).

11.11 Specific Target Organ Toxicity (Repeated Exposure): European Chemical Agency Database shows that no products of this blend to cause damage to organs due to repeat exposure, However, may cause damage to the kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

11.12 Signs and Symptoms: Effects due to exposure may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Symptoms may be delayed.

11.13 Carcinogenicity: OECD Guideline Test results found in the European Chemical Agency Database show that this product's components can cause cancer.

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Alkylate Full Range	LC50 8.2 mg/l	Fish	96 hours
Alkylate Full Range	EC50 4.5 mg/l	Daphnia	48 hours
Alkylate Full Range	EC50 3.1 mg/l	Algae	72 hours
1-Hydroxyethane	LC50 8,140 mg/l	Fish	96 hours
1-Hydroxyethane	LC50 14,221 mg/l	Daphnia	48 hours

Toxicity: OECD Guideline Test results found in the European Chemical Agency Database show this product's components to cause long-term toxicity to aquatic life.

12.2 Mobility: Floats on water.

12.3 Persistence/degradability: Inconclusive technical data.

12.4 Bioaccumulation: Inconclusive technical data.

12.5 Other adverse effects: Inconclusive technical data.

X85


Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! The container should be completely emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 Australian Transport Information



ID No.: UN 3475

Shipping Name: Ethanol and petrol mixture with more than 10% ethanol

Hazard Class: 3

Packing Group: II

Label: Flammable

Placard: Flammable

Marine Pollutant: Alkylate Full Range

HAZCHEM Code: •3YE, HIN 33

14.2 IMDG Transport Information



ID No.: UN 3475

Shipping Name: ETHANOL AND PETROL MIXTURE with more than 10% ethanol

Hazard Class: 3

Packing Group: II

Flash Point: (-43 C c.c.)

EmS Number: F-E, S-E

Label: Flammable

Placard: Flammable

Marking: Marine Pollutant, Alkylate Full Range

X85

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

14.3 UN Dangerous Goods Transport Information



ID No.: UN 3475

Shipping Name: Ethanol and petrol mixture with more than 10% ethanol

Hazard Class: 3

Packing Group: II

Label: Flammable

Placard: Flammable

Marine Pollutant: Alkylate Full Range

Section 15 - Regulatory Information

15.1

Australian manufacturers' and importers' obligations: This blend's components can be imported into Australia for commercial purposes without first notifying The Australian Government and State or Territory Government as listed in the **Australian Industrial Chemicals Introduction Scheme (AICIS)**.

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their own determination about the product's suitability for their particular purpose and on the condition that they assume the risk of their use.

16.2 References: CHEMpendium database of the Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller online, European Chemical Agency Data Base, and MSDS and SDS of chemicals in this mixture.

16.3 SDS Preparation Date 01/02/2017

SDS Previous issue Date: None

SDS Revision Date: 11/02/2020

Revised Sections: 1,2,3,8,9,11,12,13,14,15,16

Prepared by SJC Compliance Education, Inc

1319 Varese Dr.

Pearland, TX 77581

steve@sjcedu.org

END OF SAFETY DATA SHEET

