



Safety Data Sheet

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia
Date of Revision: 08/26/2022 Revision: 02

Section 1 - Chemical Product and Company Identification

1.1 Product Name: **M1**

1.2 Synonyms: Blend

1.3 Manufacture: VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

1.4 Supplier: VP Racing Fuels Pty Ltd, Unit 24 85-115 Alfred Road, Chipping Norton, NSW 2170, Australia 02 9723 4233, **Emergency Telephone:** 0421 116 838.

1.5 Recommended Use: Racing Fuels

1.6 **RESTRICTIONS on USE** **THIS FUEL IS FOR RACING VEHICLE USE ONLY!**

NOT LEGAL FOR STREET DRIVEN MOTOR VEHICLE.

1.7 Emergency Response Number: **CHEMTREC 800-424-9300**

International Emergency Telephone Number: **+1-703-527-3887**

CHEMTREC Australia (Sydney) **+(61) 290372994**

1.8 Poison Control Centre: 13 11 26, 24 hours a day from anywhere in Australia.

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes

Highly Flammable liquid/vapor

Specific Target Organs toxicity single exposure

Acute Toxicity Oral

Acute Toxicity Dermal

Acute Toxicity Inhalation

Hazard Categories

Category 2

Category 1

Category 3

Category 3

Category 3

2.2 Signal Word: **Danger**

2.3 Pictograms:



Flame



Health



Toxic



Keep away from children

M1

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

2.4 Hazard Statements

PHYSICAL HAZARDS:	H225: Highly flammable liquid and vapor.
HEALTH HAZARDS:	H301+ H311: Toxic if swallowed or in contact with skin. H331: Toxic if inhaled. H370: Causes damage to organs.
ENVIRONMENTAL HAZARDS:	None.
PRECAUTIONARY STATEMENTS:	P102: Keep out of reach of children. P203: Obtain special instructions before use. READ SDS BEFORE USE. P210: Keep away from sparks and open flames- No smoking. P223: Keep container tightly closed. P240: Ground or bond container and receiving equipment. P241: Use explosion-proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261: Avoid breathing vapors and mist. P264: Wash skin and hands thoroughly after handling. P270: Do not eat, drink, or smoke when using this product. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves, clothing, eye, and face protection.
RESPONSE STATEMENTS:	P301 +P310+P331: IF SWALLOWED: Immediately call Poison Control Centre: 13 11 26, 24 hours a day from anywhere in Australia DO NOT induce vomiting P302+P312+352: IF ON SKIN: Wash with plenty of water. Call a poison center or doctor if you feel unwell. P304+P331+P340: IF INHALED: Remove to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. P308+P311: If exposed or concerned, call a poison center or doctor. P330: Rinse mouth. P362+P364: IF ON CLOTHING, take off contaminated clothing and wash it before reuse.

M1

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

P370+ P378: In case of fire, use foam, carbon dioxide, or dry chemical to extinguish the fire.

STORAGE STATEMENTS:

**P403+P235: Store in a well-ventilated place.
Keep cool.
P405: Store locked up.**

DISPOSAL STATEMENTS:

P501: Dispose of content and container following local, regional, national, or international regulations.

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: AUH066 Repeated exposure may cause skin dryness and cracking. IF IN THE EYES: Rinse cautiously with water for at least 15 minutes.

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	Classifications
67-56-1	200-659-6	Methanol	<= 100	Flam. Liq. H225, Acute Tox. H301, Acute Tox. 3, H311, Acute Tox. 3, H331, STOT SE1 H370

3.3 Trade Secret Provision and Chemical Concentration Disclosure: In accordance with GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a range and apply to the hazards as identified in this Safety Data Sheet.

Section 4 - First Aid Measures

4.1 Description of first aid measures

4.1.1 General information: Ensure medical personnel knows the material(s) involved and take precautions to protect themselves.

4.1.2 Following Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

4.1.3 Following Skin contact: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

4.1.4 Following eye contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.1.5 Following ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.2 Most important symptoms and effects, both acute and delayed:

4.2.1: Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

4.2.2: Prolonged and repeated liquid contact with the skin can cause defatting and drying and lead to irritation and dermatitis.

M1

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

4.2.3: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities can produce chemical pneumonia, pulmonary edema, and even death.

4.2.4: Prolonged breathing of high vapor concentrations can produce headaches, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

4.3 Indication of any immediate medical attention and special treatment needed: The severity of outcome following exposure may be related to the time between the exposure and treatment rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

Note to Physicians: If you determine that a medical emergency exists. The specific chemical identity is necessary for emergency or first-aid treatment and will be immediately disclosed the specific chemical identity. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

General fire hazards: Highly flammable liquid and vapor.

5.1 Extinguishing media:

Suitable extinguishing media: Water fog. Alcohol-resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media: Do not use a water jet as an extinguisher, as this will spread the fire.

5.2 Special hazards arising from the substance or mixture: Vapors may form explosive mixtures with air. Vapors may travel a considerable distance to a source of ignition and flashback. During a fire, gases hazardous to health may be formed.

5.3 Advice for firefighters: Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

Additional information: Do not release runoff from fire to sewers or waterways.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment, and emergency procedures:

6.1.1 For non-emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spills and leaks. Take precautionary measures against static discharge. Eliminate all ignition sources. No smoking, flames, sparks, or flames in the immediate area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

6.1.2 For emergency responders: Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.

6.2 Environmental precautions: Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways.

6.3 Methods and material for containment and cleaning up:

M1

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

6.3.1 For containment: Eliminate all ignition sources (no smoking, flares, sparks, or flames in the immediate area). Keep combustibles such as wood, paper, and oil) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewers, basements, or confined areas.

6.3.2 For clean-up:

6.3.2.1 Small spill; Absorb with earth, sand, or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

6.3.2.2 Large spill: Stop the material flow if this is without risk. Contain the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand, or earth to soak up the product and place it into a container for later disposal. Following product recovery, flush the area with water.

6.3.3 Other information: Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers.

6.4 Reference to other sections: See section 8 of the SDS for personal protection. For waste disposal, see section 13 of the SDS.

Section 7 - Handling and Storage

7.1 Precautions for safe handling: Avoid breathing vapors. Avoid contact with eyes, skin, and clothing. Avoid contact with eyes. Observe good industrial hygiene practices. Provide adequate ventilation. Take precautionary measures against static discharge. Eliminate all ignition sources. No smoking, flames, sparks, or flames in the immediate area., Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Launder contaminated clothing before reuse. Avoid release to the environment. Observe good industrial hygiene practices.

7.1.1 Bonding and grounding plastic containers:

When bonding and grounding two non-conductive containers, a static electrical charge can be generated when two dissimilar materials (Metal and Plastic) pass quickly by one another. Their many factors affect the size and strength of the static charge or potential that may develop, such as speed of transfer, humidity, and container size. Therefore, the transfer of flammable liquids between plastic or other non-conductive containers should be under the following conditions:

1. A non-conductive container must be equipped with an approved metallic suction pump and draw tube for taking liquid from the top of a plastic container. The pump must be electrically grounded.
2. The non-conductive container must be equipped with a metallic, self-closing faucet that can be grounded electrically.

Additionally, flammable liquids between small containers may not require special bonding and grounding techniques. NFPA 77-1993 states that glass containers or other non-conductive materials of five gallons or less capacity are usually filled without special precautions." However, NFPA 77-1993 suggests that special techniques should handle flammable liquids in plastic containers with 5 to 60 gallons for larger containers would consider compliance with NFPA 77-1993 regarding the bonding and grounding of plastic containers holding flammable liquids.).

7.2 Conditions for safe storage, including incompatibilities: Store locked up in a cool, dry, well-ventilated place out of direct sunlight. Keep away from heat, sparks, and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a tightly-closed container. Store in a. Store away from incompatible materials (see section 10).

7.3 Specific end use(s): Racing fuel only.

M1

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OEL
Methanol	200 ppm TWA	200 ppm TWA

8.2

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.

OEL = Occupational Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

8.3 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder before reuse. Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows, air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

8.6 Protective Clothing Pictograms



Splash Goggles



Gloves



Protective Apron



Vapor Respirator

M1

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Clear

Odor: Pungent

Vapor Pressure: Not Available

Vapor Density (Air=1): >1

Specific Gravity (H₂O=1,): 0.7950

Odor Threshold: Not Available

Flammability (solid, gas): Not applicable.

Evaporation rate: Not Available

Partition coefficient octanol/water: Not Available

Water Solubility: Completely miscible

Flash Point: 9.7 °C c.c.

Boiling Point: 64.7°C

Freezing/Melting Point: Not Available

Lower Explosive Limits (vol % in air): 6%

Upper Explosive Limits (vol % in air): 36%

Viscosity: Not Available

Autoignition Temperature: Not Available

Decomposition temperature: Not Available

pH: None

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents.

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide.

10.5 Conditions to Avoid: Avoid heat, sparks, open flames, and other ignition sources.

Section 11- Toxicological Information

11.1

Product Name	Results	Species	Dose	Exposure
*Methanol	Oral LD50	Rat	50-300 mg/kg	None Listed
*Methanol	Dermal LD50	Rabbit	200-1000 mg/kg	None Listed
*Methanol	Inhalation LC50	Rat	2-10mg/l	4 hours

* Acute Toxicity Per GHS Classification Summary Tables

11.1.1 OECD Guideline Test results found in the European Chemical Agency Database show that this product's components are Acute Oral Toxicity.

11.1.2 OECD Guideline Test results found in the European Chemical Agency Database show that this product's components are Acute Inhalation Toxicity.

11.1.3 OECD Guideline Test results found in the European Chemical Agency Database show that this product's components to Acute Dermal Toxicity.

11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin and Eye Contact,

11.3 Aspiration Hazard: European Chemical Agency Database shows that no components of this product may be fatal if swallowed and enters airways.

M1

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

11.4 Mutagenicity: OECD Guideline Test results found in the European Chemical Agency Database show no components of this product to cause genetic defects.

11.5 Skin Corrosion/Irritation: OECD Guideline Test results found in the European Chemical Agency Database shows that no components of this product cause skin irritation. Repeated exposure may cause skin dryness or cracking.

11.6 Serious Eye Damage/Irritation: OECD Guideline Test results found in the European Chemical Agency Database show that no components of this product cause serious eye irritation.

11.7 Reproductive toxicity: OECD Guideline Test results found in the European Chemical Agency database show no components of this product cause damage to fertility or the unborn child.

11.8 Skin Sensitisation: OECD Guideline Test results found in the European Chemical Agency Database show no components of this product cause skin sensitivity.

11.9 Respiratory Sensitisation: OECD Guideline Test results found in the European Chemical Agency Database show no components of this product cause respiratory sensitivity.

11.10 Specific Target Organ Toxicity (Single Exposure): European Chemical Agency Database shows that components of this product may cause damage to the following organs: Eyes, Kidney, Liver, Heart, Central nervous system.

11.11 Specific Target Organ Toxicity (Repeated Exposure): None

11.12 Signs and Symptoms: Effects of overexposure can include Methyl alcohol may be fatal or cause blindness if swallowed. Effects due to ingestion may include Headache, Dizziness, Drowsiness, metabolic acidosis, Coma, Seizures. Symptoms may be delayed.

11.13 Carcinogenicity: OECD Guideline Tests results found in the European Chemical Agency Database show no components of this product to cause cancer.

Note: ACGIH—American Conference of Governmental Industrial Hygienists list Methanol as a confirmed human Carcinogen.

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Methanol	LC50 29.4 mg/L	Fish	96 hours
Methanol	LC50 22,200 mg/L	Daphnia	48 hours

Toxicity: OECD Guideline Test results found in the European Chemical Agency Database show no components of this product to be harmful cause long-term toxicity to aquatic life. **DO NOT** discharge into a sewer or waterway.

12.2 Mobility: Floats on water.

12.3 Persistence/degradability: Inconclusive technical data.

12.4 Bioaccumulation: Inconclusive technical data.

12.5 Other adverse effects: Inconclusive technical data.

M1

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! The container should be completely emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 Australian Transport Information



ID No.: UN 123G

Shipping Name: Methanol

Hazard Class: 3, (6.1)

Packing Group: II

Label: Flammable, Toxic

Placard: Flammable, Toxic

HAZCHEM Code: 3WE(3), HIN 336

14.2 IMDG Transport Information



ID No.: UN 1230

Shipping Name: Methanol

Hazard Class: 3, (6.1)


Flash Point: 9.7 °C c.c.

Packing Group: II

Label: Flammable, Toxic

Placard: Flammable, Toxic

14.3 UN Dangerous Goods Transport Information



ID No.: UN 1230

Shipping Name: Methanol

Hazard Class: 3, (6.1)

Packing Group: II

Label: Flammable, Toxic

Placard: Flammable, Toxic

M1

Conforms to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Australia

Section 15 - Regulatory Information

15.1

Australian manufacturers and importers' obligations under the WHS Regulations: All components of this product are on the Inventory or are exempt from Inventory requirements.

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

16.2 References: CHEMpendium database of the Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller online, European Chemical Agency Database, and MSDS and SDS of chemicals in this mixture.

16.3 SDS Preparation Date 03/17/2015

SDS Previous issue Date: None

SDS Revision Date: 09/14/2020 Revised Sections: 1,2,3,8,9,11,13,14,15,16

SDS Revision Date: 06/26/2022 Revised Sections: 2,4,5,6,7,9,1,16

Prepared by SJC Compliance Education, Inc.

PO Box 886

Rosharon, TX. 77583

steve@sjcedu.org

END OF SAFETY DATA SHEET