



Case/ frame color	Black
Display type	Active matrix TFT LCD, LED backlight
The diagonal dimension	32.0 "diagonal
Aspect ratio	16:9
Active Area Dimensions	698.4mm(H) x 392.85mm(V)
The display size	748.4mm(W) x441mm(H),Thickness: 68 mm
Resolution(pixel)	1920 x 1080 @ 60Hz
Display Colors	16.7M
Brightness (Standard)	400 cd/m ²
Response time (standard)	8 ms
View Angle(from center)	L/R:89/89;U/D:89/89 (Typ.)(CR≥10)
Contrast ratio (standard)	1200: 1(Typ.)
Input video formats	Analog VGA and digital DVI (optional HDMI,DP)
Input Video Signal Connector	Female head DE - 15 connector, female head DVI - D, Dual - Link connector, female head HDMI connector
Sweep frequency	Horizontal: 31.5 - 60.2 kHz; vertical: 56.3 - 75 Hz
Touch Technology	Infrared touch Touch points: 20 Touch supply voltage: 5V Touch interface: USB Touch support system: Windows, Android, linux
Power	External AC, input voltage-AC: 100-240VAC 50HZ-60HZ; input power connector specification (on the all-in-one machine)-type: pin suffix socket
Power consumption (standard)	Display only: 40W(Typ.)
Temperature	Operating: 0° C to 60° C; Storage: -20° C to 60° C
Humidity	Operating: 20% to 80% (no condensation); Storage: 10% to 90% (non-condensing)
MTBF	50,000 hours
Weight (approx.)	Net weight: 13kg(Typ.); Shipping: (15.0 kg (reference)
Warranty	1 year
OSD	Digital OSD
User Controls	OSD Button: Menu, Up, Down, Select, Power; OSD: Contrast, Brightness, Horizontal / Vertical Bits Clock, phase, call default, language (English, German, Spanish, Japanese,French); OSD Fail / Active: Power, OSD menu
OSD Remote Accessories	Optional controls (front):Menu, Up, Down, Select, Power
Mounting options	200MMX100MM wall-mounted installation; mobile bracket installation; K-type base
Explosion-proof	IK08(front)
Surface treatment	AG AR AF (Optional)
Agency Approvals	UL,cUL (Recognized), FCC, CE, CB,China RoHS CQC