

## **SAFETY DATA SHEET**

Revision Date: 16-Jun-2020 Revision Number: 3

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name FLOOR & PATIO LATEX ENAMEL LOW SHEEN BASE 3

Product Code F1223X
Alternate Product Code F1223X

Product Class Water thinned paint

Color All Recommended use Paint

Restrictions on use No information available

**Manufactured For** 

Benjamin Moore & Co., Limited

8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898

www.benjaminmoore.com/en-ca

**Manufacturer** 

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com Emergency Telephone CANUTEC: 613-996-6666

## 2. HAZARDS IDENTIFICATION

## Classification

This chemical is not considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

#### Label elements

Appearance liquid

Odor little or no odor

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

#### Other information

No information available

### Other hazards

**CAUTION:** All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

#### 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material Date HMIRA filed	
		_	Information Review Act	date exemption granted
			registry number	(if applicable)
			(HMIRA registry #)	
Barium sulfate	7727-43-7	10 - 30%	-	=
Titanium dioxide	13463-67-7	1 - 5%	-	-
Nepheline syenite	37244-96-5	1 - 5%	-	-

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret

## 4. FIRST AID MEASURES

General Advice No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15

minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

Revision Date: 16-Jun-2020

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of

water. Consult a physician if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

**Flash Point Data** 

Flash point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:

Upper flammability limit:

Not applicable

Not applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

#### **NFPA Legend**

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

**Environmental precautions**See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

#### 7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 16-Jun-2020

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Barium sulfate	TWA: 5 mg/m <sup>3</sup>	10 mg/m³ - TWA	5 mg/m³ - TWA	5 mg/m³ - TWA	10 mg/m <sup>3</sup> - TWAEV
	inhalable particulate				5 mg/m³ - TWAEV
	matter, particulate				
	matter containing no				
	asbestos and <1%				
	crystalline silica				
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	10 mg/m³ - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWAEV
			3 mg/m³ - TWA		
Nepheline syenite	N/E	N/E	N/E	10 mg/m <sup>3</sup> - TWA	N/E

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

**Engineering Measures** 

Ensure adequate ventilation, especially in confined areas.

Revision Date: 16-Jun-2020

**Personal Protective Equipment** 

**Eve/Face Protection Skin Protection** 

**Respiratory Protection** 

Safety glasses with side-shields.

Protective gloves and impervious clothing.

In case of insufficient ventilation wear suitable respiratory

equipment.

**Hygiene Measures** 

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** liquid

little or no odor Odor

**Odor Threshold** No information available

Density (lbs/gal) 10.1 - 10.5 **Specific Gravity** 1.21 - 1.26

No information available pН

Viscosity (cps) No information available Solubility(ies) No information available Water solubility No information available **Evaporation Rate** No information available

Vapor pressure No information available Vapor density No information available

Wt. % Solids 40 - 50 Vol. % Solids 30 - 40 Wt. % Volatiles 50 - 60 Vol. % Volatiles 60 - 70

VOC Regulatory Limit (g/L) < 50 **Boiling Point (°F)** 212

F1223X - FLOOR & PATIO LATEX ENAMEL LOW

**SHEEN BASE 3** 

Revision Date: 16-Jun-2020

Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0

Flash point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Lower flammability limit:

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)No information availableAutoignition Temperature (°C)No information availableDecomposition Temperature (°F)No information availableDecomposition Temperature (°C)No information availablePartition coefficientNo information available

### 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

**Incompatible Materials**No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

**Product Information** 

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eve contact** May cause slight irritation

**Skin contact** Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Sensitization No information available.

Revision Date: 16-Jun-2020

**Neurological Effects** No information available. **Mutagenic Effects** No information available. **Reproductive Effects** No information available. **Developmental Effects** No information available. No information available. Target organ effects No information available. STOT - single exposure No information available. STOT - repeated exposure Other adverse effects No information available. No information available. **Aspiration Hazard** 

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 2948 mg/kg ATEmix (inhalation-dust/mist) 8.9 mg/L

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Barium sulfate 7727-43-7	= 307000 mg/kg ( Rat )	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-

#### **Chronic Toxicity**

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide	-	

<sup>•</sup> Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

#### 12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

### **Product Information**

## **Acute Toxicity to Fish**

No information available

## **Acute Toxicity to Aquatic Invertebrates**

No information available

## **Acute Toxicity to Aquatic Plants**

No information available

## Persistence / Degradability

No information available.

#### **Bioaccumulation**

No information available.

## **Mobility in Environmental Media**

No information available.

#### Ozone

No information available

#### **Component Information**

#### **Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

## 13. DISPOSAL CONSIDERATIONS

#### **Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 16-Jun-2020

## 14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

Revision Date: 16-Jun-2020

#### 15. REGULATORY INFORMATION

#### **International Inventories**

**TSCA: United States**Yes - All components are listed or exempt.
Yes - All components are listed or exempt.

## National Pollutant Release Inventory (NPRI)

#### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

None

#### **NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

None

#### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

### 16. OTHER INFORMATION

HMIS - Health: 1 Flammability: 0 Reactivity: 0 PPE: -

#### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

Revision Date: 16-Jun-2020

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\_questions-questions\_posees-eng.php.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

**Revision Date:** 16-Jun-2020 **Reason for revision** Not available

#### **Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**