

SAFETY DATA SHEET

Revision Date: 27-Oct-2020 Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ULTRA SPEC SCUFF-X INTERIOR SEMI-GLOSS FINISH BASE 1

Product Code K4871X
Alternate Product Code K4871X

Product Class Water thinned paint

Color All Recommended use Paint

Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited

8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898

www.benjaminmoore.com/en-ca

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

Phone: 1-866-708-9180 www.benjaminmoore.com **Emergency Telephone**

CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada)

CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Reproductive toxicity Category 2

Label elements

Warning

Hazard statements

Suspected of damaging fertility or the unborn child

Revision Date: 27-Oct-2020



Appearance liquid Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name | CAS No. | Weight-% | Hazardous Material Information Review Act registry number (HMIRA registry #) | Date HMIRA filed and date exemption granted (if applicable) |
|--------------------|------------|-------------|---------------------------------------------------------------------------------------|-------------------------------------------------------------|
| Titanium dioxide | 13463-67-7 | 10 - 30% | (Filvility registry #) | - |
| Kaolin | 1332-58-7 | 1 - 5% | - | - |
| Silica amorphous | 7631-86-9 | 1 - 5% | - | - |
| Trimethylolpropane | 77-99-6 | 0.1 - 0.25% | - | - |
| Ammonia | 7664-41-7 | 0.1 - 0.25% | - | - |

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice No hazards which require special first aid measures.

Eye ContactRinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

K4871X - ULTRA SPEC SCUFF-X INTERIOR SEMI-GLOSS FINISH BASE 1

Skin Contact Wash off immediately with soap and plenty of water while

Wash on infinediately with soap and plenty of water while

removing all contaminated clothes and shoes.

Revision Date: 27-Oct-2020

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of

water. Consult a physician if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

Flash Point Data

Flash point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:

Upper flammability limit:

Not applicable

Not applicable

NFPA Health: 2 Flammability: 0 Instability: 0 Special: Not Applicable

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

K4871X - ULTRA SPEC SCUFF-X INTERIOR SEMI-GLOSS FINISH BASE 1

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental precautionsSee Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 27-Oct-2020

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

| Chemical name | ACGIH TLV | Alberta | British Columbia | Ontario | Quebec |
|------------------|------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|---------------------------------|-------------------------------|------------------------------------------------------------------------|
| Titanium dioxide | TWA: 10 mg/m ³ | 10 mg/m³ - TWA | 10 mg/m³ - TWA 3 mg/m³ - TWA | 10 mg/m³ - TWA | 10 mg/m ³ - TWAEV |
| Kaolin | TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter | 2 mg/m³ - TWA | 2 mg/m³ - TWA | 2 mg/m³ - TWA | 5 mg/m³ - TWAEV |
| Ammonia | STEL: 35 ppm TWA: 25 ppm | 25 ppm - TWA 17 mg/m³ - TWA 35 ppm - STEL 24 mg/m³ - STEL | 25 ppm - TWA 35 ppm - STEL | 25 ppm - TWA 35 ppm - STEL | 25 ppm - TWAEV 17 mg/m³ - TWAEV 35 ppm - STEV 24 mg/m³ - STEV |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Skin Protection

Respiratory Protection

Safety glasses with side-shields.

Protective gloves and impervious clothing.

In case of insufficient ventilation wear suitable respiratory

equipment.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash

Revision Date: 27-Oct-2020

thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 10.7 - 11.1

 Specific Gravity
 1.28 - 1.33

pH No information available
Viscosity (cps) No information available
Solubility(ies) No information available

Water solubility
Evaporation Rate
Vapor pressure

No information available
No information available
No information available

Vapor densityNo information availableWt. % Solids45 - 55Vol. % Solids35 - 45Wt. % Volatiles45 - 55Vol. % Volatiles55 - 65

VOC Regulatory Limit (g/L)< 50</th>Boiling Point (°F)212Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0

Flash point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Not applicable

Not applicable

Not applicable

Upper flammability limit:

Lower flammability limit:

Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

No information available

Autoignition Temperature (°C)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

No information available

No information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions

None under normal conditions of use.

Revision Date: 27-Oct-2020

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

Inhalation May cause irritation of respiratory tract.

Ingestion Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

No information available.

SensitizationNo information available.Neurological EffectsNo information available.Mutagenic EffectsNo information available.

Reproductive Effects Possible risk of impaired fertility. Possible risk of harm to

the unborn child.

Developmental EffectsNo information available.Target organ effectsNo information available.STOT - single exposureNo information available.STOT - repeated exposureNo information available.Other adverse effectsNo information available.Aspiration HazardNo information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 38210 mg/kg
ATEmix (dermal) 81600 mg/kg
ATEmix (inhalation-dust/mist) 465.4 mg/L

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--------------------------------|---------------------|----------------------|---------------------|
| Titanium dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| Kaolin 1332-58-7 | > 5000 mg/kg (Rat) | > 5000 mg/kg (Rat) | - |
| Silica amorphous 7631-86-9 | = 7900 mg/kg (Rat) | > 2000 mg/kg(Rabbit) | > 2.2 mg/L (Rat)1 h |

K4871X - ULTRA SPEC SCUFF-X INTERIOR SEMI-GLOSS FINISH BASE 1

Revision Date: 27-Oct-2020

| Trimethylolpropane 77-99-6 | = 14100 mg/kg(Rat) = 14000 mg/kg(Rat) | - | > 0.29 mg/L (Rat)4 h |
|-------------------------------|------------------------------------------|---|----------------------|
| Ammonia 7664-41-7 | = 350 mg/kg (Rat) | - | = 2000 ppm (Rat) 4 h |

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name | IARC | NTP |
|------------------|--------------------------------|-----|
| | 2B - Possible Human Carcinogen | |
| Titanium dioxide | | |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component Information

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 27-Oct-2020

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States DSL: CanadaYes - All components are listed or exempt.
No - Not all of the components are listed.

One or more component is listed on NDSL.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

 Chemical name
 CAS No.
 Weight-%
 NPRI Parts 1- 4

 Ammonia
 7664-41-7
 0.1 - 0.25%
 Listed

Revision Date: 27-Oct-2020

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

HMIS - Health: 2* Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Revision Date: 27-Oct-2020 **Reason for revision** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and

Revision Date: 27-Oct-2020

completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet