


magnum® New Zealand

magnum® are manufacturers and suppliers of quality Horse Walkers, Aqua Walkers, Horse Stables, Stable Hardware, Feed/Water Bins, Mare and Foal Crushes, Horserail and Gates for the Equine and Agricultural Industries

We have spent many years perfecting our products and work closely with our customers so you can be assured you will get what is right for you. We take pride in being innovative, flexible and committed to quality workmanship.

Over our 20 plus years of operation we have developed a solid reputation. We ensure all products bearing the 'magnum® Built' label meet our guaranteed standard of being rugged, reliable and built to last.

Magnum® are proud supporters of The CatWalk Spinal Cord Injury Research Trust and their vision of a world where spinal cord injury doesn't mean paralysis for life. For more information visit www.catwalk.org.nz.



Contents

Walkers	Claw Insulator Black	9
Horse Walkers2	Donut Tensioner Hot Cote White	9
Aqua Walkers3	Joining Buckle Hot Cote Black	9
Stable Hardware	Feeding & Watering	
Tie Up Ring4	Flush Bin	11
Flush Hay Rack XL4	Over Rail Bin	
Flush Hay Rack4	Flush Bin Auto Waterer	
Corner Hay Rack4		
Saddle Rack4	Over Rail Bin with Safety Clip	
Fold Down Cover Rack4	Over Rail Bin only	
Cover Rack4	Truck & Float Bin	
Kick Latch & Keeper4	Paddock Feeder	
Water Arm4	Non Spill Feed Bin - Corner	12
Heavy Hinge5	Non Spill Feed Bin Flush	12
Medium Hinge5	Non Spill Feed Bin Over Rail	12
Spring Bolt & D5	Feed & Water Bin & Bracket	12
Sliding Bolt & D5	Automatic Waterer 13 Ltr	12
Manure Fork5	Corner Feed Bin	13
Manure Fork XL5	Round Feed & Water Bin Over Rail	13
Clip & Corner Bracket5	Water Bucket	13
Fencing	Rotational Feed Bin Door	13
HorseRail Hot Top Plus6-7	Steel Tech Screws	13
HorseRail Hotcote8	Wood Fixing Screws	13
Top Rail Insulator Bracket9	Over Rail Bracket	13
Line Post Insulator Bracket	Corner Wall Bracket	13
White & Secure Screw9	Wall Bracket	13
Top 90deg Inside Corner Insulated Bracket9	Truck & Float Bracket	13
90deg Inside Corner Insulated Bracket Black	Flush Bracket	13
& M12 x 120 Galv Coach Screw & Washer9		
Tensioning Spooler White9	Stables	
Pre Bent 45deg Attaching Insulated	Stables	14
Buckle Black & M12 x 120 Galv	Magnaclad	15
Coach Screw & Washer9	Batten Bugle Steel Fixing	15
Fixed Insulated T-Buckle & M12 x 120	Batten Bugle Wood Fixing	15
Galv Coach Screw & Washer9	A	
M12 x 120 Galv Coach Screw & Washer9	Accessories	4.6
Joining Buckle Black9	Horse Safe Gates	
Pre Bent 45deg Attaching	Tie Ups	
Buckle Hotcote Black9	Mare & Foal Crush	17



Horse Walker

The **magnum**® Horse Walker is internationally recognised as a safe, reliable and unique monorail design. This allows your horses to be trained and exercised with minimal labour costs.

More than just a walking machine, the Magnum® Horse Walker can be used for: fitness, conditioning, strengthening, body building, toning, rehabilitation and pre training.

The walker has become a necessary tool for every day training and is used by many leading trainers, an example being Cambridge Stud, Stephen McKee, Bjorn Baker, Chris Waller, Kevin Gray, Peter & Dawn Williams, Singapore Racing Club, Royal Cavalry of Oman.

Pre trainers and agistment farms are also seeing the benefits of walking horses and the walkers are being used by leaders in the field amongst which are Lyndhurst Farms, Muskoka Farms and Breckon Farm.

The Monorail system was designed so that the walker runs in a continuous stable motion as it is fitted with both large and small nylon wheels which ensures smooth running of the machine. Each and every hinged backing gate is individually attached to the monorail to ensure the upmost safety of the horse. Backing gates can be electrified. The additional feature of the monorail system enables us to construct a purpose built roofing system significantly reducing the cost of the roof versus a cantilever design. Spouting can be added if required.

A lunging ring is available for the 20 and 25 meter walkers, fully utilizing the centre space, it comes with a complete set of internal panels. Internal and external gates allow easy access to the centre of the walker.

The mesh and rubber frame allows for greater visibility for both horse and operator when in use increasing your horse safety, it also allows increased air flow around the horses legs.

The generous bay sizes allow horses to trot on the larger machines and move freely in the space, bay sizes are 2.1 meters wide x 4 to 4.7 meters long. This allows the horse to turn around in the bay when changing direction.

The walkers are fitted with a control box with 9 variable speed options allowing them to go from 5-15 Kph, speed level 4-6 are the most commonly used settings. The walker requires 240 volts of single phase power to the control box. Control box invertor takes three phase cable to motors. All walkers are supplied with a remote control enabling the operator to start and stop as necessary, ideal for loading and unloading horses.

There are two options for the base of the walker, one being concrete curbing with sand infill, the second being a full concrete base overlaid with magnum® rubber matting.

An entranceway can be added to the outside of the walker frame adding extra weather protection for both horse and staff.

Full installation of the walker is available, we supply foundation plans for the concrete base work and electrical wiring plans.

Model Options

Deluxe – includes roof Premium – excludes roof

Size Options

25 meter – 12 – 15 horses – 2 x 1.1 kW motors 20 meter – 10 horse – 2 x 1.1 kW motors 18 meter – 9 horse – 2 x 1.1 kW motors 16 meter – 8 horse – 2 x 1.1 kW motors 12 meter – 6 horse – 1 x 1.5 kW motor

Warranty

All walkers carry a 24 month warranty on parts and labour





The magnum® Aqua Walker is based on the proven magnum® 20m Horse Walker, offering reliability and ease of operation.

Low Impact with High Resistance exercise for both fitness and rehabilitation. Designed with both horses and people's safety in mind, the magnum® Aqua Walker is a world class machine.

The Aqua Walker utilizes the magnum® Horse Walker which has a unique Monorail design which produces proven fitness results.

The Aqua Walker has become a welcome addition to the range of exercise equipment for every day training and is used by many leading trainers, an example being Eliza Park, Rogerson Racing, Kendayla Park, Pencarrow Stud and Karalee Park Stud.

The monorail system was designed so that the walker runs in a continuous stable motion with each and every gate individually attached to the monorail ensuring the utmost safety of the horse.

Supporting the monorail is a set of both large and small nylon wheels which ensure smooth running of the machine. The mesh

visibility for both horse and operator when in use increasing your horse safety. Walkers are fitted with a pedestrian safety barrier rail. All walkers are supplied with a remote control enabling the operator to start and stop as necessary, ideal for loading and unloading horses. Generous bays sizes allow horses to turn around in the bay when changing direction. The walkers are fitted with a control box with 9 variable speed options allowing them to go from 5-15 kph, for greater resistance.

The reinforced concrete construction of the pool has a smooth waterproof finish, accommodating a 2100 mm wide channel and ramp, this is also available as a 2400 mm wide option. The water level is designed to be at 1100 mm and the pool has a wall height of 1250 mm. Magnaclad baffles are fitted to 2.4 pools to increase resistance water flow. The entrance ramp allows for ease of entering and exiting the pool for all horses. A horse safe backing gate is fitted

The screen and filtration system will process 130,000 litres of water per hour via concrete suction points, this is then pumped through a stainless steel screen which will pre filter the water. From there the water will be pumped through a series of Sand Filter Tanks. The vacuum system has on mobile 2.2 kW single phase pump and can be set up to vacuum from 2 points around the pool. The water will require chlorination.

Model

20m Aqua Walker

Warranty

24 month warranty on parts and labour.



Stable Hardware



Tie Up Ring

MB26

- Zinc plated
- · Heavy duty
- · Indoor/outdoor



Flush Hay Rack XL

MB44XL

- Zinc plated
- · Two biscuit capacity
- 500h x 600w x 300d
- 5.4 kg
- Suitable indoor/outdoor



Flush Hay Rack

MB44

- Zinc plated
- · One biscuit capacity
- 500h x 600w x 200d
- Weight 4.1 kg
- · Suitable indoor/outdoor



Corner Hay Rack

MB42

- Zinc plated
- One biscuit capacity
- 750w x 600h x 100d
- Weight 2.9 kg
- Suitable indoor/outdoor



Saddle Rack

SADDLE

- Zinc plated
- 1000h x 50w x 500d
- 4.25 kg
- · Suitable for two saddles



Fold Down Cover Rack

Cover-2

- Zinc plated
- 1030w x 160d x 40h
- 1.3 kg



Cover Rack

Cover

- Zinc plated
- 600w x 150d x 50h
- 2.2 kg



Kick Latch & Keeper

MBK

- Zinc plated
- Includes leeper
- 0.8 kg



Water Arm

- Galvanised Steel including Mounting Bracket
- 540h x 1880d x 60w
- 10 kg
- Hose not included



Heavy Hinge

MB50

- Zinc plated
- 1.2 kg



Medium Hinge

MBM50

- Zinc plated
- 0.6 kg



Spring Bolt & D

MBS51

- Zinc plated
- Universal
- Heavy duty
- 1.3 kg



Sliding Bolt & D

MB51

- Zinc plated
- Universal
- 0.9 kg



Manure Fork

MB15

- Zinc plated
- Heavy duty
- Steel curved prongs
- Steel handle/rubber grip
- Anti spread bar
- 1360h x 270d x 310w
- Weight 2 kg



Manure Fork XL

MB15XL

- Zinc plated
- Heavy duty
- Steel curved prongs
- Steel handle/rubber grip
- Anti spread bar
- 1360h x 270d x 410w
- Weight 2.2 kg



Clip & Corner Bracket

MB14

- Zinc plated bracket
- Brass clip
- Holds 20 litre bucket (not included)





HorseRail

The flexibility, smoothness and strength of this rail not only protects the horse and rider from injuries caused by conventional railing, but these characteristics also provide a long lasting, attractive fence that requires little maintenance. HorseRail® is designed to be easily installed using a patented procedure for attaching, joining and tensioning. There is no stripping, crimping or notching needed and the end result is a properly installed fence with no exposed wires.

- · High Tensile Wire
- Molecularly Bonded to the wire

- Long-Life UV Stabilized
- Non-Conductive Medium Density Polyethylene

Specifications

4"3 Wire Hottop Plus 660


3 Strands of 12.5 gauge (2.5 mm) electrogalvanized ASTM class 3, pre-straightened high tensile wire, 180,000 psi, min. breaking strength 4,200 Lbs, molecularly bonded to medium density UV stabilized polyethlene plastic, pat. no. 6,533,881.

- 2 conductive strips top and bottom
- Rail width: 4.25" (108 mm)
- Thickness of webbing: .050" (1.27 mm)
- Roll length: 660' (200 m)
- Weight: 135 Lbs

- Dimensions: 38"l x 38"w x 5"h
 (97cm x 97cm x 13cm)
- Rolls per skid: 12 rolls







HorseRail costs about the same as a board fence in cash outlay. However, when the annual maintenance cost is taken into account, our rail fence is less expensive. It's the safety factor that is difficult to place a value on when it comes to the welfare of your animals.





Hotcote®

Hotcote® uses high tensile wire, coated in a highly conductive carbon compound which can deliver electric shock. It can be used as your entire fence or in conjunction with Horsecote® and/or Horserail® to create the exact look you desire.

Installation hardware features a patented procedure for attaching, joining and tensioning the coated wire providing a clean, neat look while being safe for both horse and rider. There is no stripping, crimping or notching needed and the end result is a properly installed fence with no exposed wires.

- · High Tensile Wire
- Long-Life UV Stabilized Non-Conductive
 Medium Density Polyethylene
- Highly Conductive Carbon Compound

Available Colours


- Black
- White

(All with black stripes)

Specifications

1 Strand of 12.5 gauge (2.5 mm) electrogalvanized ASTM class 3, high tensile wire, 180,000 psi, min. breaking strength 1,320 Lbs, medium density UV stabilized polyethlene plastic

- 3 conductive strips
- Overall diameter: .295" +/- .005"
- Roll length: 1320' (402 m)
- Weight: 70 Lbs
- Dimensions: 25" x 25" x 5.5" (64cm x 64cm x 14cm)
- Package: 20 rolls / pallet





Fencing Attachments

All attachments available in black or white, all fixings sold separately.



Top Rail Insulator Bracket RITBK-4



Line Post Insulator Bracket White & Secure Screw RIW-4 & STS



Top 90 deg Inside Corner Insulated Bracket IB90TBK-4



90 deg Inside Corner Insulated Bracket Black & M12 x 120 Galv Coach Screw & Washer IB90BK-4 & M12x120



Tensioning Spooler White IB90TBK-4



Pre Bent 45 deg Attaching Insulated Buckle Black & M12 x 120 Galv Coach Screw & Washer IABBK-445 & M12x120



Fixed Insulated T-Buckle & M12 x 120 Galv Coach Screw & Washer
ITBW-4 & M12x120



M12 x 120 Galv Coach Screw & Washer M12x120



Joining Buckle Black JBBK-4



Pre Bent 45 deg Attaching Buckle Hot Cote Black LCABBK-45



Claw Insulator Black CIB



Donut Tensioner Hot Cote White DTW



Joining Buckle Hot Cote Black CWJBBK





Flush Bin

MB101

- Indestructible plastic
- External lip
- 38 litre capacity
- 450w x 320h x 430d
- 2.8 kg each
- · Suitable for feed or water
- Can be fitted with bungs for water drainage
- supplied with zinc plated flush and wall brackets



Over Rail Bin

MB102

- Indestructible plastic
- External lip
- 38 litre capacity
- 450w x 320h x 500d
- 2.9 kg per bin
- Suitable for feed or water
- Can be fitted with bungs for water drainage
- Supplied with zinc plated over rail brackets



Flush Bin Auto Waterer

MB104

- Indestructible plastic
- External lip
- 30 litre capacity
- 450w x 370h x 430d
- 2.9 kg per bin
- 20 mm ballcock left or right
- 20 mm bung for easy draining
- Removable ballcock cover
- Supplied with zinc plated flush and wall brackets



Over Rail Bin with Safety Clip

MB105

- Indestructible plastic
- External lip
- 38 litre capacity
- 450w x 320h x 480d
- 2.1 kg per bin
- Stackable
- Supplied with brass safety clip
- Suitable for up to 50 mm rail



Over Rail Bin Only

MB106

- Indestructible plastic
- External lip
- 38 litre capacity
- 450w x 320h x 480d
- 2.0 kg per bin
- Stackable
- Suitable for up to 50 mm rail



Truck & Float Bin

MB109

- Indestructible plastic
- External lip
- 38 litre capacity
- 650w x 320h x 480d
- 3.2 kg per bin
- Stackable
- Supplied with zinc plated truck bracket

Feeding & Watering



Paddock Feeder

MBPF

- Indestructible plastic
- 40 litre capacity
- 800w x 800d x 200h
- Suitable feed or water
- 3.3 kg per feeder
- Centre drain hole if requested. Drain hole is molded ready for drilling out at any stage



Non Spill Feed Bin -Corner

MB5

- Internal lip
- 38 litre capacity
- 500w x 320h x 500d
- 3.2 kg per bin
- Supplied with zinc plated flush & corner brackets



Non Spill Feed Bin Flush

MB7

- Internal lip
- 38 litre capacity
- 450w x 280h x 430d
- 2.8 kg per bin
- Supplied with zinc plated flush & wall brackets



Non Spill Feed Bin Over Rail

MB9

- Internal lip
- 38 litre capacity
- 450w x 280h x 480d
- Supplied with zinc plated over rail brackets
- Suitable for up to 50 mm rail



Feed & Water Bin & Bracket

MB13

- 13 litre capacity
- 300w x 230h x 350d
- 3.3 kg per bin
- Supplied with zinc plated wall bracket



Automatic Waterer 13Ltr

MBMB13

- 13 Litre capacity
- 380w x 270h x 360d
- 4.4 kg per bin
- 20 mm ballcock left or right
- 20 mm bung for easy draining
- Removable aluminium
 ballcock cover
- Steel reinforced rub rail bracket



Corner Feed Bin

MB16

- 38 litre capacity
- 400w x 330h x 500d
- 3.2 kg per bin
- Suitable for feed or water
- Supplied with zinc plated flush and corner wall bracket



Round Feed & Water Bin Over Rail

MB17

- 38 litre capacity
- 400w x 400d x 330h
- 2.6 kg per bin
- Suitable for feed or water
- Supplied with zinc plated over rail bracket
- Suitable for up to 50 mm rail



Water Bucket

MB19

- 30 Litre capacity
- 380w x 350h x 340d
- 1.8 kg per bin
- Steel handle

Feeding & Watering Fittings



Steel Tech Screws

STS



Wood Fixing Screws

\//E



Over Rail Bracket

MBORB



Corner Wall Bracket

CORNBKT

Zinc plated, 0.6 kg



Wall Bracket

WALL

Zinc plated, 0.8 kg



Truck & Float Bracket

TKBKT



Flush Bracket

MBFB

Zinc plated, 0.6 kg





Rotational Feed Bin Door

MBRF

- Includes MB101 or MB7 Bin
- Galvanised / Magnaclad
- 500h x 770w x 60d



magnum® Stables

magnum® stables are designed and built with your horses wellbeing and safety as our major focus. No minimum quantities are required as all our stables are custom designed and built.

Options

- 12 mm vertical bars 58 mm between bars
- 50mm x 50mm x5mm welded mesh
- Magnaclad 10 mm high density polyethylene
- Anti-Weave available in either door style
- External barn doors
- Safety feed bin doors options
- Plywood 18 mm

- Strong galvanised frame
- Hinged doors
- Sliding doors
- Split doors
- Roll top fronts
- Pipe yard





Magnaclad

Magnaclad has been specifically developed for use in stables for partitions and all interior wall linings.

Options

- Standard size is 2400mm x 1200mm x 10mm
- Sheet weight 30 kg
- Other sizes available on request (min quantity requirements)
- Range of colours available (current colour light grey) - min order 250 sheets
- 100% waterproof

- High density polyethylene easy to clean and maintain
- Interior applications only
- Indestructible one face textured / one face smooth
- Environmentally friendly made from recycled material

Magnaclad Fixings



Batten Bugle Steel FixingBBSF



Batten Bugle Wood FixingBBWF



Horse Safe Gates

The magnum® Horse Safe Gate has been designed to ensure your animals will always be safe and secure.

Specifications

- magnum® can manufacture to any size
- All hot dipped galvanised
- The frame is a heavy wall 44 mm pipe & 50mm x
 50mm x 5mm welded mesh with 50mm x 25mm
 RHS uprights and 90 degree elbows to reduce the

 The magnum® Horse Safe Gates standard height is 1200 mm





Mare & Foal Crush

The **magnum**® crush has proven to be very popular with breeding studs and vets.

We provide our customers with choice and flexibility, if our standard size crush requires amendments to suit you and your vet's needs. Our team can assist you with any design changes you may wish to make.

Our mare and foal crush is manufactured with 350 grade steel RHS, galvanised and lined with Magnaclad. Padded sides are also available as an optional extra. The doors are fitted with 20 mm spring loaded pins which have a safety slam latch feature. This eliminates the sometimes frustrating task of trying to slide a manual door bolt into place with a challenging mare pushing against the door.

Tie Ups

- Heavy Duty 100 mm galvanised pipe
- Standard size is 1200h x 2400 l

• Designed and manufactured to order



Proven Track Record



magnum® Industries Ltd 171 Ellis Street Frankton Hamilton 3204 New Zealand

0800 66 55 66 07 847 55 66 magnum.co.nz