




ULTRA LIFTING RINGS

**READ SAFETY PRECAUTION PRIOR TO USE
(SAFETY INFORMATION PAGE 151)**



- 200% Proof-Load Tested with Serial Number for Traceability
- Swivels 360° - Pivots 180°
- Material: Alloy Steel
- Safety Factor: 4:1
- Magnetic Particle Inspected
- Certified Heat Treatment
- Rated at 100% from 0°-90°
- Meets or Exceeds the Requirements of EN1677-4

STANDARD										
PART NO.	RATED LOAD (LBS)	A	B	C	D	E	F	H	THREAD SIZE	WEIGHT (LBS)
44104	800	1-1/8	1-1/2	1-1/4	5/16	1/2	3.45	1.42	5/16-18	0.6
44106	1,000	1-1/8	1-1/2	1-1/4	5/16	1/2	3.45	1.42	3/8-16	0.6
44110	2,000	1-3/8	2-1/2	2-1/4	1/2	3/4	5.83	2.36	7/16-14	2.6
44112	2,500	1-3/8	2-1/2	2-1/4	1/2	3/4	5.83	2.36	1/2-13	2.6
44114	3,000	1-3/8	2-1/2	2-1/4	1/2	7/8	5.83	2.36	9/16-12	2.6
44116	4,000	1-3/8	2-1/2	2-1/4	1/2	1	5.83	2.36	5/8-11	2.6
44120	5,000	1-1/2	3	2-3/4	3/4	1-1/4	7.05	2.76	3/4-10	5.0
44122	8,000	1-1/2	3	2-3/4	3/4	1-1/2	7.05	2.76	7/8-9	5.0
44124	10,000	1-1/2	3	2-3/4	3/4	1-1/2	7.05	2.76	1-8	5.0
44146	11,000	2	3-1/2	3-1/2	7/8	2	8.90	2.90	1-1/4-7	9.0
44150	17,600	2	3-1/2	3-1/2	7/8	2-1/8	8.90	2.90	1-1/2-6	9.0
44160	22,000	2-1/2	4	4-1/2	1	3	9.45	3.67	2-4-1/2	14.0
44163	22,000	2-1/2	4	4-1/2	1	6	9.45	3.67	2-4-1/2	17.0
44166	22,000	2-1/2	4	4-1/2	1	12	9.45	3.67	2-4-1/2	22.0
44162	22,000	2-1/2	4	4-1/2	1	3	9.45	3.67	2-8	14.0
44164	22,000	2-1/2	4	4-1/2	1	6	9.45	3.67	2-8	17.0
44168	22,000	2-1/2	4	4-1/2	1	12	9.45	3.67	2-8	22.0
44170	33,000	2-3/4	5-3/16	5	1-1/4	4	11.18	4.13	2-1/2-4	24.0
44176	33,000	2-3/4	5-3/16	5	1-1/4	8	11.18	4.13	2-1/2-4	30.0
44178	33,000	2-3/4	5-3/16	5	1-1/4	12	11.18	4.13	2-1/2-4	35.0
44172	33,000	2-3/4	5-3/16	5	1-1/4	4	11.18	4.13	2-1/2-8	24.0
44177	33,000	2-3/4	5-3/16	5	1-1/4	8	11.18	4.13	2-1/2-8	30.0
44179	33,000	2-3/4	5-3/16	5	1-1/4	12	11.18	4.13	2-1/2-8	35.0

*ADDITIONAL SIZES AVAILABLE UPON REQUEST