

GENERAL PURPOSE GRADE CREPE PAPER MASKING TAPE

TYPICAL APPLICATIONS

- General purpose packaging, bundling, holding, splicing, masking and labeling for home, school and industry

ADVANTAGES AND BENEFITS

- Economical, with good performance on a variety of substrates

CONSTRUCTION

Overall Grade/Function: General Purpose
Backing: Crepe paper
Adhesive: Synthetic rubber solventless

COLOR(S)



STANDARD WIDTH(S) STANDARD LENGTH(S)

12 mm 18 mm 24 mm
36 mm 48 mm 72 mm

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	16 lbs/in width	28.0 N/10 mm
Adhesion to Stainless Steel	35 oz/in width	3.83 N/10 mm
Thickness	4.3 mils	0.11 mm
Elongation	8%	8%
Service Temperature Range	60 F to 150 F	16 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape[®] is a registered trademark of Shurtape Technologies, LLC
Form# TDS-CP-105-08/20/2014

