

MERCO TAPE – TECHNICAL DATA SHEET

Merco M925 - M926 FSK Tape Reinforced Aluminum Foil, Scrim, Kraft Tape



M926 with retail labeling



M925 with industrial labeling

Merco Tape® M925/M926 Reinforced Aluminum Foil, Scrim, Kraft (FSK) Tape is ideally suited for any HVAC application requiring reinforced strength in a cold weather environment. We make ours with a superior grade of aluminum foil with an industry standard, reinforced, tri-directional diamond patterned scrim making it blend with new and existing fibrous and sheet metal ducts. It is highly puncture and tear resistant, ensuring both durability and long life in a variety of applications and conditions. The flexible backing conforms well to curved and irregular surfaces.

Merco Tape® M925/M926 has a specially formulated high-performance, extreme cold weather solvent-based pressure-sensitive Acrylic adhesive. That adhesive is protected by single-sided PE coated silicone release kraft liner. The backing makes it easy to apply in the most body-twisting positions a contractor might find himself in.

Property	Unit of Meas.	Value	Test Method
Peel Adhesion (180°)	N/25mm	≥ 16	PSTC-1 / ASTM D3330
Tack Rolling Ball	cm	≤ 5	PSTC-6 / ASTM D3121
Tensile Strength	N/25mm	≥ 80	PSTC-31 / ASTM D3759
Elongation	%	≥ 5	PSTC-31 / ASTM D3759
Application Temp.	°F (°C)	23° to 104°F (-5 -40°C)	
Working Temp.	°F (°C)	-40° to 48°F (-40 -120°C)	

In 50 years of selling tape no one has ever asked us for 2". Accordingly, we stock 3". On the floor and ready to ship.

**Merco Tape® M925/M926 is similar to 3M/Venture 1525CW,
Shurtape AF984CT, Polyken 338, Ideal 491, Fasson/Avery Dennison 0828**

Merco Tape

Info@MercoTape.com

(845) 357-3699

Buy@MercoTape.com

www.MercoTape.com

www.ElectricalTape.com

www.MaskingTape.com