


## Professional Nuclear Grade Duct Tape



**Backing:** PE Coated Cloth  
**Adhesive:** Rubber  
**Liner:** N/A  
**Colors:** White, Yellow, Silver  
**Specifications:** Meets NRC Reg 1.38 & ASME NQA-1  
 Tested in accordance with UL 723  
**Standard Sizes:** 48mm x 55m, 72mm x 55m

### Applications

- Multiple uses in powerplants and on ships
- Heavy-duty packaging and bundling
- Color coding
- Holding dosimeters, securing clothing and gloves, wrapping pipe ends, insulation, and duct sealing

### Features

### Benefits

- |                           |   |
|---------------------------|---|
| • PE-Coated Cloth Backing | • Excellent balance of tensile strength and tearability                               |
| • Natural Rubber Adhesive | • Aggressive adhesion to rough surfaces   |
| • Low VOC Content         | • Superior holding power for hanging applications                                     |
|                           | • Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED® |

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	11.0 mils	0.279 mm	ASTM D-1000
<b>Adhesion to Steel</b>	80 oz/in	8.75 N/cm	PSTC-101
<b>Tensile Strength</b>	26 lb/in	45.53 N/cm	ASTM D-1000
<b>Operating Temperature</b>	40 to 200 °F	4 to 93 °C	
<b>Elongation</b>	21%		ASTM D-1000
<b>VOC Content</b>	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH  
 Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.