



677

Dependable. Reliable. Professional.

Stucco Pro Masking Tape



- Backing:** Polyethylene Film
- Adhesive:** Rubber
- Liner:** N/A
- Colors:** Red
- Specifications:** N/A
- Standard Sizes:** 48mm x 55m

Applications

- Stucco and plaster masking
- General purpose outdoor masking
- Bunding, wrapping, and repairs

Features

- Polyethylene Film Backing
- Natural Rubber based adhesive

Benefits

- Conformable and flexible
- Excellent durability and solvent resistance
- Withstands outdoor exposure and moisture
- High tack for a secure bond
- Repositionable & clean removal - no residue

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7.0 mils	0.178 mm	ASTM D-1000
Adhesion to Steel	45 oz/in	4.92 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.03 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Elongation	75%		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F
 Standard Shelf Life (at 25C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038
 1-800-343-7875 Fax 1-800-328-4822
 www.nashuatape.com
 12/17/15