

**Product Specifications**

<b>Style Number</b>	VV820
<b>Construction</b>	Waterproof Foamed Core
<b>Edge Profile</b>	Enhanced Integrated Bevel
<b>Nominal Dimensions</b>	7" wide, 48" long

	US Units	Metric Units
<b>Actual Product Width</b>	7.05"	18 cm
<b>Actual Product Length</b>	48.03"	122 cm
<b>Wear Layer Thickness</b>	20 mil (0.02")	0.5 mm
<b>Overall Product Thickness</b>	0.393"	10 mm
<b>Core Thickness</b>	0.256"	6.5 mm
<b>Attached Underlayment</b>	Attached Soft Step	
<b>Attached Underlayment Thickness</b>	0.138"	3.5 mm
<b>Finish</b>	UV Acrylic	
<b>Installation Methods</b>	Floating	
<b>Profile</b>	Lock N Place Clips	
<b>Country of Origin</b>	Imported	

**Packaging**

<b>Area per Box</b>	18.8 sq ft	1.74 sq m
<b>Pieces per Box</b>	8 pcs	
<b>Weight per Box</b>	31.97 lbs	14.5 kg
<b>Boxes per Pallet</b>	55 boxes	



1026 Wheat Oak

**Colors**



**Warranties**

USF Lifetime

# COREtec Original Premium VV820


## Coordinating Trim

---




**Baby Threshold\***

BT7CT | 94"



**T-Molding\***

TM7CT | 94"



**Quarter Round**

QTRCT | 94"

\*Packaged with molding track

## Stair Tread

---



**Stair Tread**

03Z70 | 48"