



QuietTorque™ 60.0 LC

Clean, Green, and Quiet!

*Electric propulsion systems engineered
and built by sailors for sailors since 2007!*

The **QuietTorque™ 60.0 LC** is recommended for boats up to 60' (LOA) and 45,000lbs displacement. Liquid cooling provides for high sustained output, ideal for hybrid applications. Typical battery size is 300 - 500Ah.

Specifications

| | |
|-------------------|-------------------|
| Motor type | 2 PMAC Brushless |
| Voltage | 96Vdc (nom) |
| Max. Input Power | 60 kW |
| Cont. Input Power | 50 kW |
| Weight | 180 lbs (82 kg) |
| Frame | Anodized Aluminum |


*Permanent magnet Alternating Current

Standard Features

| | |
|----------------|---|
| Motor Mounts | Adjustable Mounts to current engine stringers |
| Throttle | Anodized Al waterproof throttle with key & neutral lock |
| System Monitor | Programmable digital display <ul style="list-style-type: none">• State of Charge (SOC)• Voltage, Current, Power and RPM• Time to Discharge (TTD)• Programmable regeneration and max power• Programmable RH or LH propeller rotation• Programmable for flooded, AGM and LiFePO4 battery type and size |
| Shaft coupler | 4" flange (Hurth/Borg Warner) |
| Power Switch | Two position 500A GigaVac switch |
| Relay | 500amp TE Connectivity vacuum relay |
| Fuse | Class-T fuse & holder |

Why Electric Yacht

- UNPARALLELED CUSTOMER SERVICE AND ENGINEERING
- Computer generated performance projections
- Three year warranty
- Designed for customer installation



The **QuietTorque™ 60.0 LC** is very complete and includes everything needed except for batteries, battery cables and charger. Contact us directly or through one of our dealers and we will help you design a complete system to meet your particular needs.