



BATTERY SPECIFICATION SHEET



Enduro Power ProConnect Series 12V 100Ah LiFePO4 Battery

EP100BTST

Product Specifications

Basic Electrical Specification

Nominal Voltage	12.8 V
Nominal Capacity	100 Ah
Energy	1280 Wh
Resistance	≤ 25mΩ @1kHz AC
Efficiency	99%
Self Discharge	≤3% per month
Parallel Connection	4+ (call us if over 4)
Series Connection	24, 36, 48V

Charge Specification

Recommended Charge Current	10 A - 60 A
Maximum Charge Current	100 A
Recommended Charge Voltage	14.6 V
BMS Charge Voltage Cut-Off	15.0 V (3.75 ±0.025 vpc)
Reconnect Voltage	12.0 V
Balancing Voltage	13.6V

Discharge Specification

Maximum Continuous Discharge Current	100A
Peak Discharge Current	400 A (3s)
BMS Discharge Current Cut-Off	10 V
Recommended Low Voltage Disconnect	11.2 V
BMS Discharge Voltage Cut-Off	10.0 V
Reconnect Voltage	12.0 V
Short Circuit Protection	1000 μs

Temperature Specification

Discharge Temperature	-4 to 130 °F (-20 to 55 °C)
Charge Temperature	32 to 130 °F (0 to 55 °C)
Storage Temperature - 1 month	-4 to 113 °F (-20 to 45 °C)
Storage Temperature - 1 year	32 to 95 °F (0 to 35 °C)
BMS High Temperature Cut-Off	176 °F (80 °C)
Reconnect Temperature	122 °F (50 °C)
BMS Low Temperature Cut-Off (Charging)	32 °F (0 °C)
Reconnect Temperature (Charging)	41 °F (5 °C)

BMS Overview

Over Current Protection	yes
Under Voltage Protection	yes
Over Voltage Protection	yes
Overload Protection	yes
High Temperature Protection	yes
Low Temperature Protection	yes
Short Circuit Protection	yes

Certifications

MSDS Datasheet	MSDS
UN38.3	DG61
CE Certification	EN61000-6-1, EN61000-6-3
ROHS Certification	ROHS
FCC Certification	Part15B
IEC62619 documentation or 49 CFR	IEC62619 / 49 CFR 173.185
IMDG Code	UN3840 / Class 9

Mechanical Specifications

Dimensions (L x W x H)	13 x 6.5 x 8.5" (330 x 165 x 216 mm)
Weight	31 lbs (14.06 kg)
Terminal Type	M8
Terminal Torque	10 ~12 N-m
Case Material	ABS
Enclosure Protection	IP65
Cell Type - Chemistry	Prismatic - LiFePO4

