

DGE2035 / DGE2070 Palm Size Bench-type Waveform Generator



- + Up to 70MHz frequency output
- + Sampling rate: 500MSa/s
- + 14 bits (1µHz) vertical resolution
- + Waveform length at 8K points

- + Comprehensive waveform output :
- 5 basic waveforms, and 150 built-in arbitrary waveforms
- + Multi-type modulation available in AM, FM, PM, FSK, Sweep and Burst
- + SCPI and LabVIEW supported

- + LCD in 3.6 inch, 480 x 260 pixels

Performance Specifications

	DGE2035	DGE2070
Channel	2	
Frequency Output	35MHz	70MHz
Sampling Rate	500MSa/s	
Vertical Resolution	14 bits	

Waveform

Standard Waveform	sine, square, pulse, ramp, noise
Arbitrary Waveform	exponential rise, exponential fall, $\sin(x)/x$, step wave, and others, total 150 built-in waveforms

Frequency (resolution @ 1µHz)

Sine	1µHz - 35MHz	1µHz - 70MHz
Square	1µHz - 15MHz	1µHz - 20MHz
Pulse	1µHz - 15MHz	1µHz - 20MHz
Ramp	1µHz - 1MHz	1µHz - 2MHz
Noise	20MHz (-3dB, typical)	
Arbitrary Waveform	1µHz - 10MHz	

Sine Wave Spectrum Purity

Harmonic Distortion (typical (0dB))	DC - 1MHz: <-65dBc 1MHz - 35MHz: <-60dBc	DC - 1MHz: <-65dBc 1MHz - 35MHz: <-60dBc 30MHz - 70MHz: <-50dBc
Total Harmonic Distortion	< 0.2%, 10 Hz to 20 kHz, 1 Vpp	
Spurious (non-harmonic) (typical (0dB))		≤10MHz: <-70dBc >10MHz: <-70dBc + 6dB/ octave band
Phase Noise (typical (0 dBm, 10 kHz deviation))		typical (0 dBm, 10kHz offset) 10MHz: -110dBc/Hz

Performance Specifications

Square

Rise / Fall Time	<15ns	
Overshoot	< 2%	
Duty Cycle	50.0% (fixed)	
Jitter (rms)	200ps + 30ppm	

Pulse

Period	66.667ns - 1000ks	50ns - 1000ks
Pulse Width	$\geq 24\text{ns}$	
Rise / Fall Time	$\geq 15\text{ns}$	
Overshoot	< 3%	
Jitter (rms)	200ps + 30ppm	

Ramp

Linearity	$\leq 1\%$ of peak output (typical, 1kHz, 1 Vpp, 50% symmetry)	
Symmetry	0% - 100%	

Arbitrary

Waveform Length	2 points - 8K points	
Sampling Rate	125Ma/s	300Ma/s

Amplitude

into 50Ω Load	1mVpp - 10Vpp ($\leq 10\text{MHz}$) 1mVpp - 5Vpp ($\leq 70\text{MHz}$)
DC Offset Range (AD+DC)	$\pm(10 \text{ Vpk} - \text{Amplitude Vpp}/2)$ high resistance $\pm(5 \text{ Vpk} - \text{Amplitude Vpp}/2) 50 \Omega$
DC Offset Resolution	1mV or 4 digits
Load Impedance	50 Ω (typical)
DC Offset Accuracy	$\pm(1 \% \text{ of } \text{setting} + 1 \text{ mV} + \text{amplitude Vpp} \times 0.5\%)$

Modulation

Type	AM, FM, PM, FSK, Sweep and Burst
------	----------------------------------

Sweep

Trigger Source	internal, external
----------------	--------------------

Mechanical

Display	LCD, in 3.6 inch, 480 x 260 pixels
Communication Interface	USB Host
Dimensions (W/H/D)	200 x 74.5 x 68.5 (mm)
Device Weight	0.45 kg

Accessories



Power Cord



Adapter



Manual



USB Cable



BNC Cable



BNC to Alligator Clip