



801 JUNIOR



603 JUNIOR



TORCH LIGHT



HOLSTER WITH  
MAGNET



TEST LEAD  
GRIPPER

TRMS, Auto Ranging, 6000 Counts LCD with Backlight, Torchlight, APO, Capacitance, Frequency, Duty Cycle, NCV, Temperature & Holster with Magnet

**Ranges**

<b>DC Voltage</b>	60 / 600mV / 6 / 60 / 600 / 1000V
Accuracy	± (0.8% rdg + 5 dgt)
<b>AC Voltage</b>	60 / 600mV / 6 / 60 / 600 / 750V
Accuracy	± (1.0% rdg + 10 dgt) on 60 / 600mV ± (1.0% rdg + 4 dgt) on all other ranges
AC Response	40Hz ~ 1KHz
<b>DC Current</b>	60 / 600mA / 6 / 10A
Accuracy	± (1.2% rdg + 4 dgt) on 60 / 600mA ± (3.0% rdg + 2 dgt) on 6A ± (5.0% rdg + 10 dgt) on 10A
<b>AC Current</b>	60 / 600mA / 6 / 10A
Accuracy	± (1.5% rdg + 3 dgt) on 60 / 600mA ± (3.0% rdg + 5 dgt) on 6A ± (5.0% rdg + 10 dgt) on 10A
AC Response	40Hz ~ 1KHz
<b>Resistance</b>	600Ω / 6 / 60 / 600KΩ / 6 / 60MΩ
Accuracy	± (0.8% rdg + 5 dgt)
<b>Capacitance</b>	60.00 / 600.0nF / 6.000 / 60.00 / 600.0μF / 6.000 / 60.00 / 100.0mF
Accuracy	± (3.0% rdg + 5 dgt) on all ranges except ± (5.0% rdg + 20 dgt) on 60.00 nF ± (5.0% rdg + 5 dgt) on 60.00 / 100.0 mF
<b>Frequency</b>	60.00 / 600.0Hz / 6.000 / 60.00 / 600.0KHz / 6.000 / 10.00MHz
Sensitivity	1V to 36V AC
Accuracy	± (1.5% rdg + 5 dgt)
<b>Duty Cycle</b>	1% ~ 99%
Accuracy	± (1.5% rdg + 5 dgt)
<b>Temperature</b>	-20°C ~ 1000°C / -4°F ~ 1832°F

Manual Ranging, 2000 Counts LCD with Backlight, Torchlight, APO, NCV, HFE & Holster with Magnet

**Ranges**

<b>DC Voltage</b>	200mV / 2 / 20 / 200 / 1000V
Accuracy	± (0.5% rdg + 5 dgt)
<b>AC Voltage</b>	200 / 750V
Accuracy	± (1.2% rdg + 10 dgt)
AC Response	40Hz ~ 400Hz
<b>DC Current</b>	200mA / 10A
Accuracy	± (1.0% rdg + 5 dgt) on 200mA ± (3.0% rdg + 2 dgt) on 10A
<b>AC Current</b>	200mA / 10A
Accuracy	± (3.0% rdg + 2 dgt)
AC Response	40Hz ~ 400Hz
<b>Resistance</b>	200Ω / 2 / 200KΩ / 2 / 20MΩ
Accuracy	± (1.0% rdg + 3 dgt)
<b>Measuring Category</b>	CAT II 600V
<b>SP Function</b>	Diode Test, Data Hold, Continuity Test / NCV Test with Audible as well as visible (LED) indication

Accuracy	± (1.0% rdg + 3 dgt)
<b>Measuring Category</b>	CAT II 600V
<b>SP Function</b>	Diode Test, Data Hold, Continuity Test / NCV Test with Audible as well as visible (LED) indication Three 1.5V 'AAA' Battery '☒' is indicated 200 hours typical 147 x 71 x 45mm (approx.) 230gms Including Battery (approx.)
<b>Power</b>	
<b>Low Battery</b>	
<b>Battery Life</b>	
<b>Dimensions</b>	
<b>Weight</b>	
<b>Accessories</b>	Test Leads (Pair), Holster, Battery (installed), Instruction Manual & K Type Thermocouple (upto 260°C)

<b>Power</b>	Three 1.5V 'AAA' Battery
<b>Low Battery</b>	'☒' is indicated
<b>Battery Life</b>	200 hours typical
<b>Dimensions</b>	147 x 71 x 45mm (approx.)
<b>Weight</b>	230gms Including Battery (approx.)
<b>Accessories</b>	Test Leads (Pair), Holster, Battery (installed) & Instruction Manual

**Accessories**

K Type Bead Probe (upto 260°C)  
Model : TP-K-B



K Type Stick Probe (upto 500°C)  
Model : TP-02



Pair of Test Leads suitable for DMM/DTT  
Model : TL-DMM/DTT



Pair of Test Leads suitable for Insulation Tester  
Model : TL-IT

