

KOLD-DRAFT®

STILL THE ONLY CUBE OF ITS KIND.



Plumbing:

- 3/4" FPT potable water inlet
- 3/4" FPT bin drain
- 3/4" I.D. flex tubing cuber drain
- 3/8" FPT condenser (liquid-cooled) inlet
- 1/2" FPT condenser (liquid-cooled) outlet

Exterior Finish:

300 Series stainless steel

Refrigeration System:


Thermostatic expansion valve controlled R-404A-HFC

Clearance Requirements:

Allow 4" left side, 8" right side and back, and 6" top for ventilation and utility connections.

Condenser Heat Rejection:

BTUH/kW/Ton
13,850/4.06/1.15 avg.
18,000/5.3/1.5 peak



1 1/4" x 1 1/4" x 1 1/4"

STILL THE ONLY CUBE OF ITS KIND.

X-SERIES GBX1060 – ICE MACHINE

THE X-SERIES SIGNATURE

Produces up to 1,000lbs of ice per day! The X-Series from Kold-Draft features rounded corners, plastic top panels, plastic louvers and an LCD display. X-Series machines are stackable with other X-Series machines. Double the capacity in the same footprint!

Dimensions/Weight

Description	Dimensions / inches (cm)			Ship Weight
	W	D	H	
Air Cooled	42.3" (107.4cm)	31.1" (79cm)	33.7" (85cm)	360lb (163.3kg)
Liquid Cooled	42.3" (107.4cm)	25.7" (65.3cm)	33.7" (85cm)	320lb (145kg)
Remote	42.3" (107.4cm)	25.7" (65.3cm)	33.7" (85cm)	320lb (145kg)

Recommended Operating Requirements:

	MIN.	MAX.
Room Temp.	45°F (7°C)	110°F (43°C)
Water Temp.	45°F (7°C)	90°F (32°C)
Voltage 208-230	198V	253V
Voltage 115	104V	126V
Potable Water Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)
Liquid-Cooled Condenser Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)

GTX1060 Series Daily Capacities: Lbs. of ice per 24 hours per unit

Model Number	Electrical Volt/Hz/Ph	Condenser	Cube Size	Ice Capacity 24 Hours lbs. (kg)		Energy Input 90°F (32°C) / 70°F (21°C) kWh/100 lbs. (kJ/kg)	Water Use gal/100# (l/kg) 90°F (32°C) / 70°F (21°C)		MCA	MOP	Required Condenser
				70°F (21°C) Ambient/Water	90°F (32°C) Ambient/Water		Potable	Condenser			
GBX1064AC	208-230/60/1	Air Cooled	Full Cube	1075 (488)	860 (390)	4.9 (389)	12.9 (1.1)	n/a	11	20	n/a
GBX1064LC	208-230/60/1	Liquid Cooled	Full Cube	1047 (475)	918 (416)	4.1 (325)	16.4 (1.4)	174 (14.5)	10	20	n/a
GBX1064RC	208-230/60/1	Remote Air Cooled	Full Cube	959 (435)	767 (348)	5.3 (421)	12.6 (1.1)	n/a	11	25	RC314APV

Compatible Storage Bins

Model	Width	Depth	Height (w/ 6" legs)	Capability (lb)	Weight (lb)
KDB650	42"	35"	41"	650	182
KDB950	48"	31.75"	50"	950	230

Accessories

Model Number	Description	Shipping Weight (lb)
102149501	GBX560/GBX1060 Series on top of GBX560/GBX1060 Series Stacking kit	5
DR3-GB	GB/GBX Series Drain Riser Kit, 3"	20

KOLD-DRAFT recommends all ice machines have water filtration. Please reference water filtration specification sheet.



KOLD-DRAFT • 101 Corporate Woods Parkway, Vernon Hills, IL 60061
(800) 840-9577 • info@kold-draft.com • www.kold-draft.com

an Ali Group Company



The Spirit of Excellence

KD SS GBX1060 072021