

# X-SERIES

## GTX360 – ICE MACHINE

### THE X-SERIES IMPACT

Produces up to 300lbs of ice per day! The X-Series from Kold-Draft features rounded corners, plastic top panels, plastic louvers and an LCD display. X-Series machines are stackable with other X-Series machines. Double the capacity in the same footprint!

| Dimensions/Weight |                          |                |                |                |
|-------------------|--------------------------|----------------|----------------|----------------|
| Description       | Dimensions / inches (cm) |                |                | Ship Weight    |
|                   | W                        | D              | H              |                |
| Air Cooled        | 30.1" (76.5cm)           | 25.7" (65.3cm) | 16.9" (42.9cm) | 175lb (79.3kg) |
| Liquid Cooled     | 30.1" (76.5cm)           | 25.7" (65.3cm) | 16.9" (42.9cm) | 175lb (79.3kg) |

### Recommended Operating Requirements:

|                                  | MIN.              | MAX.               |
|----------------------------------|-------------------|--------------------|
| Room Air Temp.                   | 45°F (7°C)        | 110°F (43°C)       |
| Water Temp.                      | 45°F (7°C)        | 90°F (32°C)        |
| Voltage 208-230                  | 198V              | 253V               |
| Voltage 115                      | 104V              | 126V               |
| Potable Water Pressure           | 20 PSIG (137 kPa) | 100 PSIG (689 kPa) |
| Liquid-Cooled Condenser Pressure | 20 PSIG (137 kPa) | 100 PSIG (689 kPa) |

### GTX360 Series Daily Capacities: Lbs. of ice per 24 hours per unit

| Model Number | Electrical Volt/Hz/Ph | Condenser     | Cube Size | Min. Ice Capacity 24 Hours lbs. (kg)   |  | Max. Energy Input 90°F (32°C) 70°F (21°C) kWh/100 lbs. (kJ/kg) | Max. Water Use gal/100# (l/kg) 90°F (32°C) 70°F (21°C) |            | MCA  | MOP | Required Condenser |
|--------------|-----------------------|---------------|-----------|--|--|--|--|------------|------|-----|--------------------|
|              |                       |               |           | 70°F (21°C) 50°F (10°C) Ambient/ Water | 90°F (32°C) 70°F (21°C) Ambient/ Water |  | Potable  | Condenser  |      |     |                    |
| GTX361AC     | 115/60/1              | Air Cooled    | Full Cube | 352 (160)                              | 282 (128)                              | 6.5 (516)  | 25.9 (2.2)   | n/a        | 12.0 | 15  | n/a                |
| GTX361AHK    |                       |               | Half Cube | 372 (169)                              | 286 (130)                              | 6.5 (516)  | 22.0 (1.8)   |            | 12.0 | 15  |                    |
| GTX361LC     |                       | Liquid Cooled | Full Cube | 358 (162)                              | 304 (138)                              | 5.2 (413)  | 19.5 (1.6)   | 170 (14.2) | 11.1 | 15  |                    |
| GTX361LHK    |                       |               | Half Cube | 410 (186)                              | 367 (166)                              | 4.9 (389)  | 21.0 (1.8)   | 185 (15.4) | 11.1 | 15  |                    |
| GTX364AC     | 208-230/60/1          | Air Cooled    | Full Cube | 357 (162)                              | 310 (141)                              | 6.2 (492)  | 21.3 (1.8)   | n/a        | 6.5  | 15  |                    |
| GTX364AHK    |                       |               | Half Cube | 389 (176)                              | 317 (144)                              | 6.3 (500)  | 21.3 (1.8)   |            | 6.5  | 15  |                    |
| GTX364LC     |                       | Liquid Cooled | Full Cube | 349 (158)                              | 295 (134)                              | 5.2 (413)  | 19.3 (1.6)   | 168 (14.0) | 6.0  | 15  |                    |
| GTX364LHK    |                       |               | Half Cube | 399 (181)                              | 351 (159)                              | 4.9 (389)  | 22.0 (1.8)   | 175 (14.6) | 6.0  | 15  |                    |

Use Model # GTX367AHK, GTX367AC, GTX367LHK, GTX367LC to Indicate 220/50/1.

# KOLD-DRAFT

ice Machines • bins • crushers • dispensers



### Plumbing:

- 3/4" FPT potable water inlet
- 3/4" FPT bin drain
- 3/4" I.D. flex tubing cuber drain
- 3/8" FPT condenser (liquid-cooled) inlet
- 1/2" FPT condenser (liquid-cooled) outlet

### Exterior Finish:

300 Series stainless steel

### Refrigeration System:


Thermostatic expansion valve controlled R-404A-HFC

### Clearance Requirements:

Allow 4" left side, 8" right side and back, and 6" top for ventilation and utility connections.

### Condenser Heat Rejection:

BTUH/kW/Ton  
4,700/1.38/0.39 avg.  
5,850/1.71/0.49 peak



IT'S NICE TO BE NOTICED™

