

# X-SERIES

## GTX360 – ICE MACHINE

### THE X-SERIES IMPACT

Produces up to 300lbs of ice per day! The X-Series from Kold-Draft features rounded corners, plastic top panels, plastic louvers and an LCD display. X-Series machines are stackable with other X-Series machines. Double the capacity in the same footprint!

Dimensions/Weight				
Description	Dimensions / inches (cm)			Ship Weight
	W	D	H	
Air Cooled	30.1" (76.5cm)	25.7" (65.3cm)	16.9" (42.9cm)	175lb (79.3kg)
Liquid Cooled	30.1" (76.5cm)	25.7" (65.3cm)	16.9" (42.9cm)	175lb (79.3kg)

### Recommended Operating Requirements:

	MIN.	MAX.
Room Air Temp.	45°F (7°C)	110°F (43°C)
Water Temp.	45°F (7°C)	90°F (32°C)
Voltage 208-230	198V	253V
Voltage 115	104V	126V
Potable Water Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)
Liquid-Cooled Condenser Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)

### GTX360 Series Daily Capacities: Lbs. of ice per 24 hours per unit

Model Number	Electrical Volt/Hz/Ph	Condenser	Cube Size	Min. Ice Capacity 24 Hours lbs. (kg)		Max. Energy Input 90°F (32°C) 70°F (21°C) kWh/100 lbs. (kJ/kg)	Max. Water Use gal/100# (l/kg) 90°F (32°C) 70°F (21°C)		MCA	MOP	Required Condenser
				70°F (21°C) 50°F (10°C) Ambient/ Water	90°F (32°C) 70°F (21°C) Ambient/ Water		Potable	Condenser			
GTX361AC	115/60/1	Air Cooled	Full Cube	352 (160)	282 (128)	6.5 (516)	25.9 (2.2)	n/a	12.0	15	n/a
GTX361AHK			Half Cube	372 (169)	286 (130)	6.5 (516)	22.0 (1.8)		12.0	15	
GTX361LC		Liquid Cooled	Full Cube	358 (162)	304 (138)	5.2 (413)	19.5 (1.6)	170 (14.2)	11.1	15	
GTX361LHK			Half Cube	410 (186)	367 (166)	4.9 (389)	21.0 (1.8)	185 (15.4)	11.1	15	
GTX364AC	208-230/60/1	Air Cooled	Full Cube	357 (162)	310 (141)	6.2 (492)	21.3 (1.8)	n/a	6.5	15	
GTX364AHK			Half Cube	389 (176)	317 (144)	6.3 (500)	21.3 (1.8)		6.5	15	
GTX364LC		Liquid Cooled	Full Cube	349 (158)	295 (134)	5.2 (413)	19.3 (1.6)	168 (14.0)	6.0	15	
GTX364LHK			Half Cube	399 (181)	351 (159)	4.9 (389)	22.0 (1.8)	175 (14.6)	6.0	15	

Use Model # GTX367AHK, GTX367AC, GTX367LHK, GTX367LC to Indicate 220/50/1.

# KOLD-DRAFT

ice Machines • bins • crushers • dispensers



### Plumbing:

- 3/4" FPT potable water inlet
- 3/4" FPT bin drain
- 3/4" I.D. flex tubing cuber drain
- 3/8" FPT condenser (liquid-cooled) inlet
- 1/2" FPT condenser (liquid-cooled) outlet

### Exterior Finish:

300 Series stainless steel

### Refrigeration System:


Thermostatic expansion valve controlled R-404A-HFC

### Clearance Requirements:

Allow 4" left side, 8" right side and back, and 6" top for ventilation and utility connections.

### Condenser Heat Rejection:

BTUH/kW/Ton  
4,700/1.38/0.39 avg.  
5,850/1.71/0.49 peak



IT'S NICE TO BE NOTICED™

