SC200 SERIES - SELF CONTAINED ICE MACHINE

THE KOLD-DRAFT SC200

The KOLD-DRAFT SC200 produces up to 200 lbs. of full cube ice per day. The SC200 is ideal for any undercounter or bar application. The front breathing inlet and discharge allows for installation in tight spaces.

Dimensions/Weight							
Description	D	Ship Weight					
	W	D	Н	Ship Weight			
Air Cooled (without legs)	26" (66cm)	28.6" (72.6cm)	31.4" (79.8cm)	185lb (84kg)			
With Legs	26" (66cm)	28.6" (72.6cm)	37.4" (100cm)	185lb (84kg)			

Recommended Operating Requirements:

	MIN.	MAX.
Room Temp.	45°F (7°C)	90°F (32°C)
WaterTemp.	45°F (7°C)	90°F (32°C)
Voltage 220-240	210	250
Voltage 115	104	126
Potable Water Pressure	5 PSIG (0.034 MPA)	100 PSIG (0.6 MPA)

	SC200	SC200 Series Daily Capacities: Lbs. of ice per 24 hours per unit										
	Model	Model Electrical Volt/	Condenser	Cube		apacity rs lbs. (kg)	Energy Input 90°F/70°F	Tier	Water Use gal/100# (I/kg) 90°F/70°F		MCA	MOP
	Number Hz/Ph	Size	70°F (21°C) / 50°F (10°C) Ambient/Water	90°F (32°C) / 70°F (21°C) Ambient/Water	kWh/100# (kJ/kg)	riei	Potable	Condenser	rica	rior		
	SC201AC	115/60/1	Air Cooled	Full Cube	150 (68.04)	119 (53.98)	8.71 (691.28)	1	29.56 (2.47)	n/a	6	15
	SC207AC	220-240/50/1	Air Cooled	Full Cube	149 (67.59)	118 (53.52)	8.25 (654.77)		29.34 (2.45)		3	15

KOLD-DRAFT.

ice Machines • bins • crushers • dispensers



Features:

- Produces up to 200 lbs. of full cube ice per day.
- Ideal for any undercounter or bar application.
- Front breathing inlet and discharge allows installation in tight spaces.
- Front access to ice. Door lifts up or slides in, so it's out of the way.
- Electroless nickel plated evaporator.
- Corrosion-resistant stainless steel exterior with plastic door and bin liner.
- Stores 125 lbs. of ice.

Plumbing:

1/2" FIP potable water inlet3/4" FIP ice bin drain1/2" FIP ice maker drain.88" Diameter electrical connection

Exterior Finish:

Corrosion-resistant stainless steel exterior with plastic door and bin liner









