

# SUMGAS LS (61 - 125 Ton)



## INGREDIENTS

Ethyl Alcohol (CAS # 64-17-5) 100%

## SPECS

Physical state: liquid

Appearance: clear

Odor: odorless

Freezing point: -114.14 °C (1173.45 °F)

Boiling point: 78.29 °C (172.92 °F)

Flash point: 13 °C (55.40 °F)

Auto temperature -ignition: 363 °C (685.40 °)

Relative density / Specific gravity: 0.7893 g / cm<sup>3</sup> at 20 °C

## NOTES

- Concentrated
- Compatible with all refrigerants except ammonia
- Compatible with all oils
- No need to drain systems, no need for large or sophisticated equipment, bulky tools. Injection hoses are a thing of the past

Sealing leaks will save energy and reduce refrigerant emissions.  
SUMGAS® **LEAK SEALANT** will:

- Travel with gas and is fast and effective in finding leaks
- Continue to circulate and seal leaks in the system as long as it maintains a charge in the refrigerant
- Seal most leaks and small holes

## APPLICATIONS

- Split and Mini Split A/C
- Microchannel coils
- Compact units
- Heat Pumps



Will seal most leaks / will seal most small holes in the condenser located in the condenser



Prevents the accumulation of acid



Converts moisture into synthetic lubricant



Absorbs moisture

