

SUMGAS V2



INGREDIENTS

Liquefied Petroleum Gas (CAS No) 68476-85-7

SPECS

Physical state: gas

Appearance: clear and colorless gas

Odor: odorless

Freezing point: -151.67°C (305°F)

Boiling point: -46.67°C (52°F)

Auto-ignition temperature: 467.22°C (873°F)

Vapor pressure: 861 .SkPa (125psi) at 22.1°C (70°F)

Relative vapor density at 20 ° C: 1.52

Relative density / Specific gravity: 0.5066 (water = 1)

Lower flammability limit: 2.15%.

Upper flammability limit: 9.6%.

NOTES

Do not breathe gas. Make sure there is adequate ventilation. Close the valve after each use and, when empty, open it slowly to avoid pressure surges. Regarding hygiene measures, it must be handled in accordance with appropriate industrial hygiene and safety procedures. Wash your hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

APPLICATIONS

- Heat Pumps
- Split and Mini Split A/C

Load amount: 40%

EQUIVALENT

170 Gr **SUMGAS V2** = 425 Gr R22, R407 and R401

5.5 Kg **SUMGAS V2** = 13.75 Kg R22, R407 and R401

