



### Key features

- Live view, recording & playback up to 12 MP resolution
- Up to 16 channel IP cameras can be connected with built-in PoE inputs
- Advanced H.265+ Video Compression
- Supports iPhone、 iPad、 Android mobile remote monitoring
- Connectable to the third-party network cameras
- HDMI Video output at up to 4K (3840 × 2160) resolution
- 2 SATA interfaces connectable for recording and backup
- Annke Vision for easy remote view
- Support 4-ch Human and vehicle targets detection

**Model Number**

**N46PCK**

### NVR

Video & Audio	Video Compression	H.264+/H.264/H.265/H.265+
	IP Video Input	16CH PoE
	Video Output	HDMI up to 4K, VGA up to 1080p
	Audio Input/Output	1/1 RCA
	Incoming/Outgoing Bandwidth	160/80 M
	Max. Recording Resolution	Up to 12MP(4096 X 3072)@30fps(Frame rate depends on IP camera)
	Max. Playback Resolution	Up to 12MP(4096 X 3072)@30fps(Frame rate depends on IP camera)
	Max. Playback Channel	16CH
	Max. Playback Capacity	1-ch@12 MP(4096 X 3072) (30 fps)/3-ch@4 MP (30 fps)/6-ch@1080p (30 fps)
Hard Drive	HDD	2 SATA Interface
	HDD Capacity	Up to 8 TB Capacity for each disk
External Interface	Network Interface	RJ45 X1 (10/100/1000 M)
	PoE	16, RJ-45 10/100 Mbps self-adaptive Ethernet interface, IEEE 802.3 af/at
	USB	2X USB 2.0
Smart Function	Deep learning	16-ch Human and vehicle targets detection(Need IP camera support) 4-ch Human and vehicle targets detection(IP camera does not need to support this function but the resolution cannot exceed 4MP)
	Smart Event	Line crossing detection, intrusion detection, region entrance detection, region exiting detection(Need IP camera support)
General	Operating Power	AC 100-240 V
	Power Consumption	≤15 W (Without HDD and PoE)
		PoE: Max. 25.5W for Single Port
	Working Temperature	14 °F — 131 °F/-10 °C — 55 °C
	Dimensions (W X H X D)	15.2" X 12.4" X 2.0"/385 X 315 X 52 mm
Weight (Without Hard Disk)	6.6 lbs./3 kg	
<b>Packaging Contents</b>		
	NVR	1
	USB Mouse	1
	Power Cable	1
	1M network cable	1
	1.8M HDMI cable	1
	User's Manual For NVR	1